

1 LOCATION OF WATER WELL:		Fraction <u>SW 1/4 NW 1/4 NW 1/4</u>		Section Number <u>22</u>	Township Number <u>28S</u>	Range Number <u>4E</u>
County: <u>Sedgewick</u>		Distance and direction from nearest town or city street address of well if located within city? <u>See below</u>				
2 WATER WELL OWNER: <u>Kevin & Carolyn Jantz</u>		Board of Agriculture, Division of Water Resources				
RR#, St. Address, Box # : <u>4848 S. 35th W.</u>		Application Number:				
City, State, ZIP Code : <u>Onawa, KS</u>						
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>65</u> ft. ELEVATION:				
		Depth(s) Groundwater Encountered: 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: <u>8</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>20</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: <u>11</u> in. to <u>65</u> ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes. No. <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No				
		5 TYPE OF BLANK CASING USED:				
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued. <u>X</u> Clamped. 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded Blank casing diameter in. to <u>10</u> ft., Dia. in. to ft., Dia. in. to ft. Casing height above land surface: <u>12</u> in., weight <u>240</u> lbs./ft. Wall thickness or gauge No. <u>160psi</u>				
		TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) ft.				
SCREEN-PERFORATED INTERVALS: From <u>10</u> ft. to <u>65</u> ft., From ft. to ft.		GRAVEL PACK INTERVALS: From <u>8</u> ft. to <u>65</u> ft., From ft. to ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From <u>3</u> ft. to <u>8</u> ft., From ft. to ft., From ft. to ft.				
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well 11 Fuel storage 15 Oil well/Gas well 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <u>South</u> How many feet? <u>60</u>				
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
<u>0</u>	<u>20</u>	<u>sand</u>				
<u>20</u>	<u>65</u>	<u>shale</u>				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>6-24-03</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. <u>38</u> This Water Well Record was completed on (mo/day/yr) <u>6-24-03</u> under the business name of <u>Weninger Drilling Inc.</u> by (signature) <u>Michael George</u>						