

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: SEDESWICK		SE 1/4 SE 1/4 NW 1/4	8	T 28 S	R 4N E/W
Distance and direction from nearest town or city street address of well if located within city? Southeast corner of Santa Fe & Lincoln - Chevey					
2 WATER WELL OWNER: FARMERS CO-OP ELEVATOR COMPANY					
RR#, St. Address, Box # : PO BOX 340			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : CHEVEY KS 67025			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 36.7 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 17.80 ft. below land surface measured on mo/day/yr 7/30/04			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) ☒ Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No ☒ ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes No ☒					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
☒ 2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
			7 Fiberglass		Threaded ☒
Blank casing diameter 2 in. to 26.7 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 33.0 in., weight lbs./ft. Wall thickness or gauge No. sch 40					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless Steel	5 Fiberglass	☒ 7 PVC	10 Asbestos-Cement
2 Brass		4 Galvanized Steel	6 Concrete tile	8 RMP (SR)	11 Other (Specify)
				9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		☒ 3 Mill slot 10/20	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify)	
SCREEN-PERFORATED INTERVALS: From 26.7 ft. to 36.7 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 24.3 ft. to 36.7 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout ☒ 3 Bentonite 4 Other					
Grout Intervals: From 2 ft. to 24.3 ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	☒ 16 Other (specify below) Runoff from Santa Fe
Direction from well? North How many feet? Runoff from Santa Fe					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Top soil	0	1	Cement cap
1	2	Silt, brown	1	2	soil
2	15	clay, lt gray	2	24.3	3R BENTONITE CHIPS
15	36.7	Shale - weathered, red & brown w/green @ depth	24.3	36.7	10/20 SAND

RECEIVED

SEP 03 2004

BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) **7/14/04** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. **645** This Water Well Record was completed on (mo/day/yr) **8/4/04** under the business name of **Matt Well Environmental** by (signature) **James E. Hill**