	WATER WE	LL RECORD	Form	WWC-5	KSA 82a-12	212		
1 LOCATION OF WATER WELL:	FRACTION		SECTION NUMB			RANGE NUMBER		
Sedgwick	SE 1/4		W 1/4	5	T	28 S	R 4W	E/W
Distance and direction from nearest town or city 800 N. Marshall St.	Cheney, Kansa	•						
	ENEY HIGH SO		#268)	· · · · · · · · · · · · · · · · · · ·				
	N. Marshall St.		,			Board of Ag	iculture, Division of Wa	ter Resource
CITY, STATE: Che	ney, Kansas			ZIP CODE:		Application Nu	mber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	DEPTH OF PINE	GEOFIL:	100	ft.	ELEVATION			
	pth of groundwater E	ncountered:		ft.		ft.		ft.
	ELL'S STATIC WATE	ER LEVEL 18	FT. E	BELOW LAND S	SURFACE MEAS	SURED ON mo/	day/yr: 6/19/	15
NW NE	•		ll water was		ft. after		s of pumping @	gpm
M High	Est. Yield: Bore Hole Diameter	gpm We in.	ell water was		ft. after ft. and		s of pumping @	gpm ft.
	ELL WATER 1625			_	n. and	in. 9. Dewater	to _{ina} 11. Inject	
1 1 200 1 22 1 1		edlot 5. Publi	c water su	ply 7. Lawn	and garden or	J. Dewater	12. Other (Spe	
	-			ipply 8. Air co		10. Monitori	_	
	Vas a chemical/bacteriol ibmitted	ogical sample submitte	ed to Departm		Water Well Disi	=	what mo/day/yr wa	
5 TYPE OF CASING USED:	5. Wrought Iro	on 7. Fiberg	dace	9. Other (Speci	fy below) CA	ASING JOINTS:	Glued	Threaded
1. Steel 3. RPM (SI	R) -			(.,,			Clamped
2. PVC 4. ABS	6. Asbestos-C				_			
Blank casing diameter 6	in. to	ft., Dia		n. to	ft.,	Dia.	in. to	ft.
Casing height DE Pland surface:	72 in.,	Weight	:	lbs. / ft.	Wall	thickness or gau	ge No.	
TYPE OF SCREEN OR PERFORATION 1. Steel 3. Stainless Steel	5. Fiberglass	7. PVC		9. ABS	11. (Other (specify)	N/A	
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)								
SCREEN OR PERFORATION OPENING	GS ARE:							
1. Continuous slot 3. Mill sl	ot 5. Ga	uzed wrapped		7. Torch cut	9. Dr	illed holes	11. None (op	en hole)
2. Louvered shutter 4. Key p	unched 6. Wii	re wrapped		3. Saw cut	10. Ot	her (specify) N	7/ A	
SCREEN - PERFORATION INTERVAL	From	ft.	to	ft.,	From		4-	
	From	ft.	to	ft.,	From	ft. ft.	to	ft.
GRAVEL PACK INTERVALS:	From	ft.	to	ft.,	From	ft.	to to	ft. ft.
	From	ft.	to	ft.,	From	ft.		
6 GROUT MATERIALS: 1. Neat	cement	2. Cement Grout		3. Bentonit			to conite hole plug	ft.
Grout Intervals: From 6		20	om	ft. to	ft.,	From	ft. to	≨ ft.
What is the nearest source of possible or	7 D	it priva	10 Live					
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage						15. Oil well/Gas well 16. Other (specify below)		
N/						N/A		
3. Watertight sewer line 6. Seepa Direction from well?	ge pit 9. F	eed yard	IZ. Fell	inzer storage	How n	nany feet?	- 1/1-	
	LITHOLOGIC I	LOG	Fro	m To	1		GIC LOG	
				6	compacted topsoils			
			6		hentonite hole plug			
			3	100	chlorinate	d sand and g	ravel	
					1			
								
					-			P-7
7 Contractor's or Landowner's Certific	cation: This water we	ll was 1. constru	icted 2.	reconstructe	ed or 3.	plugged	under my jurisdictio	n and
was completed on (mo/day/year)	6/19/2015	and this red	cord is true t	o the best of my	knowledge and	belief.		
Kansas Water Well Contractor's Licens	se No. 236	This wat	er well recor	d was complete	ed on (mo/day/ye	ear) 6/22	/2015	
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp								