KOLAR Document ID: 1416660

	WELL R			WWC-5		vision of Wat					
		Correction		e in Well Use		ources App.			Well ID		
1 LOCATION OF WATER WELL: Fraction					ction Numb	1 0					
County: 1/4 1/4 1/4											
						treet or Rural Address where well is located (if unknown, distance and					
Business: di Address:						irection from nearest town or intersection): If at owner's address, check here:					
Address:											
City:			State:	ZIP:							
3 LOCAT	E WELL	4.000					_				
WITH "X" IN 4 DEPTH OF COMPLETED WELL:											
SECTIO	SECTION BOX: Depth(s) Groundwater Encountered: 1)										
1	N 2) ft. 3) ft., or 4)							WGS 84 INAI		IAD 27	
				n. yr)			Latitude/Longitude unit make/model:		`		
NW	NIE			yr)			WAAS enabled?				
19 W		Pump test d					Survey		10)		
w		-	hours				e Mapper:				
CW			Well v								
SW	SE		hours	gpm	6 Elevation & Crowd Level TOC						
		Estimated Y				6 Elevation:ft. Ground Level TOC					
	S	Bore Hole I			Source	Source: Land Survey GPS Topographic Map					
1 mile in. to ft.											
7 WELL WATER TO BE USED AS:											
	1. Domestic: 5. Public Water Supply: well ID C. D. Durataina have a super supply: well and a super supply and a super supply in the super supply and a super supply in the super super supply in the super super supply in the super super										
	□ Household 6. □ Dewatering: how many wells? □ Lawn & Garden 7. □ Aquifer Recharge: well ID										
	Livestock X. Monitoring: well ID										
	2. □ Irrigation 9. Environmental Remediation: well ID .						12. Geothermal: how many bores?a) Closed Loop □ Horizontal □ Vertical				
3. 🗌 Feedlo			Air Sparge					Loop 🗌 Surface Di			
	4. Industrial Recovery Injection						13. \Box Other (specify):				
Was a chemical/bacteriological sample submitted to KDHE? Yes No If yes, date sample was submitted:											
Water well disinfected? Ves No											
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded											
Casing diameter in. to ft., Diameter in. to ft., Diameter in. to ft.											
Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No											
TYPE OF SCREEN OR PERFORATION MATERIAL:											
$\Box \text{ Steel} \qquad \Box \text{ Stainless Steel} \qquad \Box \text{ PVC} \qquad \Box \text{ Other (Specify)} \dots$											
□ Brass □ Galvanized Steel □ None used (open hole)											
SCREEN OR PERFORATION OPENINGS ARE:											
Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify)											
Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole)											
SCREEN-PERFORATED INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft.											
GRAVEL PACK INTERVALS: From ft. to ft., From ft. to ft., From ft. to ft. to ft.											
9 GROUT MATERIAL: Neat cement Cement grout Bentonite Other											
Grout Intervals: From ft. to ft., From ft. to ft., From ft. to ft.											
	rce of possibl			potential source of cont					1.0		
□ Septic □ Sewer			Lateral Line			Livestock P			cide Storage		
	Lines ight Sewer Lir		Cess Pool	☐ Sewage Lag ☐ Feedyard		Fuel Storage Fertilizer St			ll/Gas Well		
			Seepage Pit			rennizer St	orage		n/Gas well		
Other (Specify) Direction from well? ft.											
10 FROM	TO		ITHOLOG		FROM	ТО		HO. LOG (cont.) or		GINTERVALS	
	<u> </u>						1				
	<u> </u>						1				
							1				
							1				
							1				
	<u> </u>				Notes:	1	1				
11 CONT	11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged										
under my j	urisdiction ar	nd was compl	eted on (n	no-day-year)	and	this record	is tru	e to the best of m	y knowled	ge and belief.	
Kansas Wa	ter Well Con	tractor's Lice	ense No	This Wa	ter Well Red	cord was co	mple	ted on (mo-day-ye	ear)		
under the b	usiness name	<u>e of</u>				·····					
KS Donorte				ELL OWNER and retain o						785-206 3565	
KS Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-3565. Visit us at http://www.kdheks.gov/waterwell/index.html KSA 82a-1212											