

1 LOCATION OF WATER WELL:		Fraction		Form WWU-5		KSA 82a-1212	
County: Sedgewick		NE 1/4 NW 1/4 SE 1/4		Section Number 5		Township Number T 28 S	
Range Number R 4 EW							
Distance and direction from nearest town or city street address of well if located within city?							
City							
2 WATER WELL OWNER: Mark Schmidtberger							
RR#, St. Address, Box #: Box 358							
City, State, ZIP Code: Cheney, KS. 67025							
Board of Agriculture, Division of Water Resources							
Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:							
N		W		E		S	
NW		NE		SW		SE	
		X					
4 DEPTH OF COMPLETED WELL: 85 ft. ELEVATION: 27 ft. 27 ft. 60 ft. 78 ft.							
WELL'S STATIC WATER LEVEL: 27 ft. below land surface measured on mo/day/yr 2-13-91							
Pump test data: Well water was ft. after hours pumping gpm							
Est. Yield gpm: Well water was ft. after hours pumping gpm							
Bore Hole Diameter: 10 in. to 85 ft. and in. to ft.							
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
2 Irrigation 4 Industrial Lawn and garden only 10 Monitoring well							
Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted							
Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped							
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded							
7 Fiberglass Threaded							
Blank casing diameter 5 in. to 45 ft. Dia in. to ft. Dia in. to ft.							
Casing height above land surface 18 in. weight lbs./ft. Wall thickness or gauge No. SDR 36							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)							
12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes							
7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 45 ft. to 85 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 20 ft. to 85 ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Cement Grout Plug							
Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)							
13 Insecticide storage							
Direction from well? N.W. How many feet? 40							
FROM TO		LITHOLOGIC LOG		FROM TO		PLUGGING INTERVALS	
0 2		Soil					
2 8		Red Clay					
8 85		Red Shale					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-13-91 and this record is true to the best of my knowledge and belief. Kansas							
Water Well Contractor's License No. 395 This Water Well Record was completed on (mo/day/yr) 4-11-91							
under the business name of Craig Roberts Co. by (signature) Craig Roberts							
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.							