

1 LOCATION OF WATER WELL:		Fraction	Township Number	Range Number	
County: Sedgewick NE ¼ SE ¼ SW ¼		Section Number 8	Township Number T 28 S	Range Number R 4 EW	
Distance and direction from nearest town or city street address of well if located within city? 827 N. Lincoln					
2 WATER WELL OWNER:	Terry Voth RR#, St. Address, Box #: 827 N. Lincoln Box 532 City, State, ZIP Code : Cheney KS. 67025				
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 88 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 32 ft. 2. 60 ft. 3. 80 ft. WELL'S STATIC WATER LEVEL . 28 ft. below land surface measured on mo/day/yr 4-2-90 Pump test data: Well water was _____ ft. after _____ hours pumping _____ gpm Est. Yield _____ gpm; Well water was _____ ft. after _____ hours pumping _____ gpm Bore Hole Diameter . 10 in. to 88 ft., and _____ in. to _____ ft.				
N S					
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:	CASING JOINTS: Glued Clamped Welded Threaded				
1 Steel 3 RMP (SR)	5 Wrought iron 8 Concrete tile				
2 PVC 4 ABS	6 Asbestos-Cement 9 Other (specify below)				
Blank casing diameter . 5 in. to 48 ft., Dia . in. to .ft., Dia . in. to .ft.	7 Fiberglass				
Casing height above land surface . 18 in., weight lbs./ft. Wall thickness or gauge No. SDR 26					
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 48 ft. to 88 ft. From .ft. to .ft. .ft. to .ft. .ft. to .ft. .ft. to .ft. GRAVEL PACK INTERVALS: From 20 ft. to 88 ft. From .ft. to .ft. From .ft. to .ft. .ft. to .ft. .ft. to .ft.					
6 GROUT MATERIAL:	Bariod - Hole Plug				
Grout Intervals: From 0 ft. to 20 ft. From .ft. to .ft. From .ft. to .ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) How many feet? 40					
Direction from well? North					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Soil			
3	19	Clay			
19	88	Red Shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-2-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 395 This Water Well Record was completed on (mo/day/yr) 6-2-90 by signature Craig Roberts Co.					

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.