		WELL:			1/4 NE		; Section Nu ; 14				-	
			nearest	town or	city street OF JOHNSON.							
WATER WE	LL OWNER:	V Box # : 5	/AN FLOYI)			Boar					
City, St	ate, ZIP o	ode : I	DENVER, I	(S 80	203-		App]	lication Nu	mber: 2087	7		
	ELL'S LOCA N SECTION				4 DEPTH OF COMPLETED WELL 330 ELEVATION: 0 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft.				t. 3.	0 f		
\	1 1 1 1	NE	i .		S STATIC WAT Pump te		200 ft. b Well water i				no/day/yr s pumping	
;	NW	X		Estim	ated Yield	0 gpm:	: Well water	was 0	ft. after	0 hour	s pumping	0 (
	i 		<u>:</u>	E Bore	Hole Diamete	er	in. t	o 0 ft.	, and	in. to	0 ft.	
1	; ;	: ! SE		WELL	WATER WAS: (02 IRRIGAT	rio n					į
:		! ! ! !	i i		chemical/bass, mo/day/yr						ell disint	fected?
TYPE OF Blank ca Casing h	BLANK CAS asing diam neight abo	ING USED: (eter : ve land sur	01 STEEL 16 in rface	. to 33 -48 in.,	CASING 50 ft., Dia weight	6 JOINTS: in	WELDED . to 0 f		in. to	o 0 ft.		
TYPE OF Blank ca Casing h TYPE OF	BLANK CAS asing diam neight abov SCREEN OR	ING USED: (01 STEEL 16 in rface ON MATER	. to 33 -48 in., IAL: 01 S	CASING 60 ft., Dia Weight STEEL	6 JOINTS: in	WELDED . to 0 f	t., Dia	in. to	o 0 ft.		
TYPE OF Blank ca Casing h TYPE OF SCREEN O	BLANK CAS asing diam neight abo SCREEN OR OR PERFORA	ING USED: (eter : ve land sur PERFORATIO	01 STEEL 16 in rface ON MATER NGS ARE:	. to 33 -48 in., IAL: 01 S UNKN	CASING 80 ft., Dia weight STEEL HOWN 0 ft. to	G JOINTS: in 0 lbs	WELDED . to 0 f s/ft. Wall, From	t., Dia thickness (O ft. to	in. to or gauge No O ft.	o 0 ft.		
TYPE OF Blank ca Casing h TYPE OF BCREEN O	BLANK CAS. asing diam neight abov SCREEN OR PERFORA	ING USED: (eter : ve land sui PERFORATION OPENII	01 STEEL 16 in rface ON MATER NGS ARE:	. to 33 -48 in., IAL: 01 S UNKN	CASING SO ft., Dia weight STEEL IOWN O ft. to 0 ft. to 0 ft. to	S JOINTS: in 0 lbs	WELDED . to 0 f s/ft. Wall ., From	t., Dia thickness (O ft. to O ft. to O ft. to	in. to or gauge No 0 ft. 0 ft. 0 ft.	o 0 ft.		
TYPE OF Blank ca Casing h TYPE OF GCREEN O GREEN P GR	BLANK CAS. asing diam neight abov SCREEN OR PERFORATE PERFORATED RAVEL PACK	ING USED: (eter : : : : : : : : : : : : : : : : : : :	01 STEEL 16 in rface ON MATER NGS ARE: :	. to 33 -48 in., IAL: 01 S UNKN From From From From	CASING Reight STEEL HOWN Oft. to Oft. to Oft. to Oft. to	O ft O ft O ft	WELDED to 0 f s/ft. Wall , From , From , From , From	t., Dia thickness of 0 ft. to 0 ft. to 0 ft. to 0 ft. to	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft.	0 ft.		
TYPE OF Blank ca Casing h TYPE OF SCREEN O GREEN P GROUT MA GROUT In What is	BLANK CAS. asing diam neight abov SCREEN OR PERFORATED RAVEL PACK ATERIAL atervals:	ING USED: (eter : ve land sui PERFORATION OPENII INTERVALS INTERVALS O2 CEMENT From : st source (O1 STEEL 16 in rface ON MATER NGS ARE: : : GROUT 3 ft. to	. to 33 -48 in., IAL: 01 S UNKN From From From From	CASING SO ft., Dia weight STEEL IOWN O ft. to 0 ft. to 0 ft. to	O ft O ft. to	WELDED . to 0 f s/ft. Wall ., From ., From ., From ., From	t., Dia thickness (O ft. to O ft. to O ft. to	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft.	0 ft.		
YPE OF Slank ca Casing h YPE OF SCREEN O GREEN P GROUT MA GROUT In	BLANK CAS. asing diam neight abor SCREEN OR PERFORATED RAVEL PACK ATERIAL ntervals: the neares	ine used: (eter : ; ve land sui PERFORATION OPENIO INTERVALS INTERVALS O2 CEMENT From : st source (11?	O1 STEEL 16 in rface ON MATER NGS ARE: : : GROUT 3 ft. to of possi	. to 33 -48 in., IAL: 01 S UNKN From From From From	CASING SO ft., Dia weight STEEL IOWN O ft. to	O ft O ft. to	WELDED . to 0 f s/ft. Wall ., From ., From ., From ., From ., From ., From	t., Dia thickness of Oft. to Oft. to Oft. to Oft. to , From	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft.	0 ft.	low many	feet?
YPE OF Slank ca Casing h YPE OF SCREEN O GREEN P GROUT MA GROUT MA Grout In	BLANK CAS. asing diam neight abor SCREEN OR PERFORATED RAVEL PACK ATERIAL ntervals: the neares	ine used: (eter : ; ve land sui PERFORATION OPENIO INTERVALS INTERVALS O2 CEMENT From : st source (11?	O1 STEEL 16 in rface ON MATER NGS ARE: : : GROUT 3 ft. to of possi	. to 33 -48 in., IAL: 01 S UNKN From From From From From From	CASING SO ft., Dia weight STEEL IOWN O ft. to	O ft O ft. to	WELDED . to Off s/ft. Wall ., From ., Store St	t., Dia thickness (Oft. to Oft. to Oft. to Oft. to TO TO 13	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft.	0 ft.	low many	feet?
YPE OF Slank ca Casing h YPE OF SCREEN O GREEN P GROUT MA GROUT MA Grout In	BLANK CAS. asing diam neight abor SCREEN OR PERFORATED RAVEL PACK ATERIAL ntervals: the neares	ine used: (eter : ; ve land sui PERFORATION OPENIO INTERVALS INTERVALS O2 CEMENT From : st source (11?	O1 STEEL 16 in rface ON MATER NGS ARE: : : GROUT 3 ft. to of possi	. to 33 -48 in., IAL: 01 S UNKN From From From From From From	CASING SO ft., Dia weight STEEL IOWN O ft. to	O ft O ft. to	WELDED . to 0 f 5/ft. Wall ., From ., From ., From ., From . FROM . 0 . 3 . 13 . 200	t., Dia thickness (Oft. to Oft. to Oft. to Oft. to Oft. to I TO I 3 I 13 I 200 I 330	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft. CEMENT (CLAY	0 ft. PLUGGING	low many	feet?
YPE OF Slank ca Casing h YPE OF SCREEN O GREEN P GROUT MA GROUT MA Grout In	BLANK CAS. asing diam neight abor SCREEN OR PERFORATED RAVEL PACK ATERIAL ntervals: the neares	ine used: (eter : ; ve land sui PERFORATION OPENIO INTERVALS INTERVALS O2 CEMENT From : st source (11?	O1 STEEL 16 in rface ON MATER NGS ARE: : : GROUT 3 ft. to of possi	. to 33 -48 in., IAL: 01 S UNKN From From From From From From	CASING SO ft., Dia weight STEEL IOWN O ft. to	O ft O ft. to	WELDED . to 0 f 5/ft. Wall ., From ., From ., From ., From ., From ., From ., 200 ., 3 ., 200 ., 0	t., Dia thickness of thickness of the too of	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft. CEMENT (CLAY CHLORING	0 ft. PLUGGING	low many	feet?
TYPE OF Slank ca Casing h TYPE OF GCREEN OF GCREEN P GROUT MA Grout In What is Directio	BLANK CAS. asing diam neight abor SCREEN OR PERFORATED RAVEL PACK ATERIAL ntervals: the neares	ine used: (eter : ; ve land sui PERFORATION OPENIO INTERVALS INTERVALS O2 CEMENT From : st source (11?	O1 STEEL 16 in rface ON MATER NGS ARE: : : GROUT 3 ft. to of possi	. to 33 -48 in., IAL: 01 S UNKN From From From From From From	CASING SO ft., Dia weight STEEL IOWN O ft. to	O ft O ft. to	WELDED . to 0 f 5/ft. Wall ., From ., From ., From ., From ., From ., From ., I a a a a a a a a a a a a a a a a a a	t., Dia thickness (in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft. CEMENT (CLAY CHLORING	0 ft. PLUGGING	low many	feet?
TYPE OF Blank ca Casing h TYPE OF SCREEN O	BLANK CAS. asing diam neight abor SCREEN OR PERFORATED RAVEL PACK ATERIAL ntervals: the neares	ine used: (eter : ; ve land sui PERFORATION OPENIO INTERVALS INTERVALS O2 CEMENT From : st source (11?	O1 STEEL 16 in rface ON MATER NGS ARE: : : GROUT 3 ft. to of possi	. to 33 -48 in., IAL: 01 S UNKN From From From From From From	CASING SO ft., Dia weight STEEL IOWN O ft. to	O ft O ft. to	WELDED . to 0 f 5/ft. Wall ., From ., From ., From ., From ., From ., From ., 200 ., 3 ., 200 ., 0	t., Dia thickness of thickness of the too of	in. to or gauge No 0 ft. 0 ft. 0 ft. 0 ft. CEMENT (CLAY CHLORING	0 ft. PLUGGING	low many	feet?

completed on (mo/day/year) 11/26/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 145 This Water Well Record was completed on (mo/day/yr) 02/04/92

under the business name of HENKLE DRILLING & SUPPLY

by (signature) Douglas A. Herble