

CORRECTION(S) TO WATER WELL RECORD (WWC-5)

(to rectify lacking or incorrect information)

Location listed as:

Section-Township-Range: _____

Fraction ($\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$): _____

County: Stanton

Location changed to:

31-285-41W

NW NW NW

Other changes: Initial statements: Morton County

Changed to: Stanton County

Comments: _____

verification method: Written & legal descriptions, and
Stanton County ownership map.

initials: DRd date: 11/9/2004

submitted by: Kansas Geological Survey, Data Resources Library, 1930 Constant Ave., Lawrence, KS 66047-3726
to: Kansas Dept of Health & Environment, Bureau of Water, 1000 SW Jackson, Suite 420, Topeka, KS 66612-1367.

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Fraction Section Number Township Number Range Number
 COUNTY: MORTON NW 1/4 NW 1/4 NW 1/4 31 T 28 S R 41 W

Distance and direction from nearest town or city street address of well if located within city?
 FROM JOHNSON CITY - 6 MILES WEST ON OLD 160 HIGHWAY

2 WATER WELL OWNER: WARTMAN, GREG
 RR#, St. Address, Box #: 220 N. COLLAGE Board of Agriculture, Division of Water Resources
 City, State, ZIP code: ULYSSES, KS 67880- Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

1	2	3	4
W	X	SW	SE
NE	SE	SW	SE

4 DEPTH OF COMPLETED WELL 356 ELEVATION: 0
 Depth(s) Groundwater Encountered 1. 0 ft. 2. 0 ft. 3. 0 ft.

WELL'S STATIC WATER LEVEL 210 ft. below land surface measured on mo/day/yr 08/23/04
 Pump test data: Well water was 0 ft. after 0 hours pumping 0 gpm
 Estimated Yield 25 gpm: Well water was 0 ft. after 0 hours pumping 0 gpm
 Bore Hole Diameter 9 in. to 356 ft., and in. to 0 ft.
 WELL WATER TO BE USED AS: DOMESTIC
 Was a chemical/bacteriological sample submitted to department? No ;
 If yes, mo/day/yr sample was submitted Water well disinfected? Yes

5 TYPE OF BLANK CASING USED: PVC CASING JOINTS: GLUED
 Blank casing diameter 5 in. to 356 ft., Dia in. to 0 ft., Dia in. to 0 ft.
 Casing height above land surface 12 in., weight 200 lbs/ft. Wall thickness or gauge No. 17
 TYPE OF SCREEN OR PERFORATION MATERIAL: PVC
 SCREEN OR PERFORATION OPENINGS ARE: SAW CUT

SCREEN PERFORATED INTERVALS: From 270 ft. to 350 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 GRAVEL PACK INTERVALS: From 25 ft. to 356 ft., From 0 ft. to 0 ft.
 From 0 ft. to 0 ft., From 0 ft. to 0 ft.

6 GROUT MATERIAL BENTONITE
 Grout Intervals: From 5 ft. to 25 ft., From 0 ft. to 0 ft., From 0 ft. to 0 ft.
 What is the nearest source of possible contamination: ABANDONED WELL
 Direction from well? EAST How many feet? 20

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	20	01 TOPSOIL 05 CLAY 10 FINE-MEDSAND			
20	40	10 FINE-MEDSAND 32 TAN CLAY			
40	80	10 FINE-MEDSAND 32 TAN CLAY 19 LAYERS			
80	140	02 FINE SAND 32 TAN CLAY 19 LAYERS			
140	200	10 FINE-MEDSAND 32 TAN CLAY 19 LAYERS			
200	280	37 FIN-COAR SAN 32 TAN CLAY 19 LAYERS			
280	300	02 FINE SAND 05 CLAY 29 SANDSTONE			
300	340	29 SANDSTONE			
340	360	08 ROCK LAYERS 05 CLAY 07 BLUE SHALE			

RECEIVED
 OCT 27 2004
 BUREAU OF WATER

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Constructed under my jurisdiction and was completed on (mo/day/year) 08/24/04 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 179 This Water Well Record was completed on (mo/day/yr) 08/31/04 under the business name of JOB'S WELL SERVICE, INC. by (signature) *Justin Cuck*