WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors)
Topeka, Kansas 66620

| | | | | | | ТОР | eka, Kansas 00020 | |
|------------------------|-----------------------------------|-----------------|----------|--------------|--------|-------------------------------------------------|-----------------------|---------------------------------------------|
| 1 1 N F H | County | Fraction | | Section | number | Township number | Range number | |
| 1. Location of well: | Stanton | NE1/4 SE 1/4 SW | 7 1/4 | 16 | | т 2 8 s | r 41 | E.W |
| | ection from nearest town or city: | | 3. Ow | ner of well | : Le | ster Canny | | |
| 3 N & 2 | W of Johnson, | KS | R.R. o | r street: | R | FD | | |
| Street address of well | i location it in city: | | City, s | itate, zip d | ode: , | Johnson, KS | 67855 | |
| 4. Locate with "X" | in section below: | Sketch map: | | | | 6. Bore hole dia. 26 in | . Completion date _ | <u> 11/1</u> 4/75 |
| ١ | | • | | | | Well depth 348 ft. | · . | I |
| Ŧ . | | | / | / | | 7 Cable tool Rotary | Driven Duc | |
| | we. | ll Drilled ll | 1/13, | /75 | | Hollow rod Jetted | | |
| [t | | | | | | 8. Use: Domestic P | | ndustry |
| Mile Mile | E . | | | | | | ir conditioning S | , |
| F 1 | | | | | | Lawn O | il field water. C | Other |
| sw | SE | | | | | 9. Casing: Materia Stee | LiHeight: Above or | below |
| | i | | | | | Threaded Welded X | | |
| | 5 | | | | | RMP PVC | Weight4_1 | lbs./ft. |
| ı 1 № | Aile ———— | | | | | Dia. 16 in. to 34 8. des | oth Wall Thickness: i | nches or |
| 5. Type and color of | f material | | | From | To | Dia in. to ft. dep | th gage Noe | 250 |
| | | | | | | 10. Screen: Manufacturer's Johnson | nome | · · · · · · · · · · · · · · · · · · · |
| See 3 | ttachment | | | | | | | |
| 500 1 | ic cacime ne | **** | <u>.</u> | | | TypeContinuous Slot/gouze .100 | 10 | |
| | | | | | | Set between 280 | _ Length | |
| | | | | | | ft. | | |
| | | • | | | | Gravel pack? Yes Size ro | inge of material | <u>/8-1/</u> 4" |
| | | | | | | 11. Static water level: | mo | o./day/yr. |
| | | · | | - | | ft. below land su | rface Date 11/ | 14/75 |
| | | | | | | 12. Pumping level below lan | d surfaces: | _ |
| | | | | | | | | |
| | | | | | | ft. after | hrs.pumping | |
| | | | | | | Estimated maximum yield — | | g.p.m. |
| | | • | | | | 13. Water sample submitted: Yes X No | Date | o./day/yr. |
| | • | , | | | | | Dale | |
| | | | | | | 14. Well head completion: Pitless adapter | 12 Inches above | e grade |
| | | " | | | | 15. Well grouted? Yes | | |
| | | | | | | With: Neat cement _X | Bentonite | Concrete |
| | | | | | | Depth: FromO ft. to | | l¯l∝ |
| | | | | | | 16. Nearest source of possible | e contamination: | none |
| | 17 | | | | | The Direction — | | |
| | | | | <u> </u> | | Well disinfected upon compl | | <u></u> ₩ 1 |
| | | | | | | 17. Pump: | X Not installed | ~ |
| | | | | + | | Manufacturer's name Model number | HP Vo | |
| | | | | | | Length of drop pipe | | _g.p.m. (冬) |
| | | ···· | | 1 | | Type: | supscii, | -• |
| | | | | | | Submersible | Turbin | ne . |
| | | | | | | Jet | | rocating |
| | (Use a second s | heet if needed) | | | | Centrifugal | Other | |
| 18. Elevation: | 19. Remarks: | | | | | 20. Water well contractor's | | 10` |
| F1-+ | | | | | | This well was drilled under m | • • | is report |
| Flat Topography: | | | | | | is true to the best of my know Henkle Drilli | - | المتعاد بروم |
| Hill | | | | | | | | ceuse the |
| Slope | | | | | | Business name BOX 639 | GardenCi | CA'KR |
| Upland | | | | | 9 | Signed A Box | Russon | 11.24 7 |
| Valley | i | | | | • | Authorized re | presentative | \lambda \bar{\bar{\bar{\bar{\bar{\bar{\bar{ |

DRILLERS TEST LOG

CUSTOMERS NAME Lester Canny DATE 11-6-75 STREET ADDRESS_ _TEST 🚁 📴 CITY & STATE Johnson, Kansas DRILLER Livingston COUNTY Stanton QUARTER SW SECTION 16 TOWNSHIP 25 RANGE 41

LOCATION 800' north of the SE corner of the SW14

| % | DRILLED | FOOTAGE | | WELL LOCATION Static Water Level | | | | | | |
|-----|---------------------|----------------|------|------------------------------------------------|--|--|--|--|--|--|
| | | | To | Description of Strata Proposed Well Depth | | | | | | |
| | 0 | | 2 | Top soil | | | | | | |
| 1 7 | 2 | | 60 | Sandy clay & fine sand | | | | | | |
| | 60 | | 96 | Sand fine & few clay st. | | | | | | |
| | 96 | | 140 | Sand fine to med & few clay st. | | | | | | |
| | 140 | | 200 | Sand fine to med coarse, small gravel | | | | | | |
| | 2002 | | 210 | Cemented sand | | | | | | |
| 3.4 | 210 | | 217 | Brown sandy clay & sand | | | | | | |
| 85 | 217 | 62 | 287 | Sand fine to med coarse, small to med brown & | | | | | | |
| | | | | white gravel, white & tan rock, very few cemen | | | | | | |
| | | | | ledges & clay st. | | | | | | |
| | 2 8 7 | | 339 | Brown clay | | | | | | |
| ery | 330 | 15 | 345 | Sandstone & very few clay st, used lots of wat | | | | | | |
| boo | 345 | | 365 | Soapstone, yellow & gray | | | | | | |
| | 365 | | 370 | Weathered shale | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | Section 1 | | | | | | | | | |
| | 14 | | 7 | TOTAL DEPOSIT OF LINES 2404 | | | | | | |
| | | | | TOTAL DEPTH OF WELL 348' | | | | | | |
| | | | | 176.1 | | | | | | |
| | | | **** | Set up west | | | | | | |
| | | | | Dig pit on the north | | | | | | |
| 1 4 | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | 7 | | | Install 40' of Johnson Screen | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | that is got to | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | $\neg +$ | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | - | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |
| | | | | | | | | | | |

HONE 276-3278

ARDEN CITY, KANSAS HENKLE DRILLING & SUPPLY CO., INC. SUBLETTE, KANSAS IRRIGATION HEADQUARTERS PHONE 675-4311