WATER WELL RECORD Form WWC-5 Division of Water NEW SE WNE WAY W 13 Resources App. No. Original Record Correction Change in Well Use Well ID Range Number 1 LOCATION OF WATER WELL: R & DE DW County: Singman

2 WELL OWNER: Last Name: Green

Business: 10995 58 2011 First John Street or Rural Address where well is located (if unknown, distance and direction from nearest town or intersection): If at owner's address, check here: Murdock State: Ko ZIP: 67/11 City: 4 DEPTH OF COMPLETED WELL: 100 ft. 3 LOCATE WELL 5 Latitude: 37. 61601447. (decimal degrees) Depth(s) Groundwater Encountered: 1)3.3.... ft. WITH "X" IN Longitude: 97. 918 2.7.539 (decimal degrees) SECTION BOX: Detum: WGS 84 · NAD 83 NAD 27 N Source for Latitude/Longitude: GPS (unit make/model:) (WAAS enabled? ☐ Yes ☐ No) -- NE --☐ Land Survey ☐ Topographic Map after...... hours pumping gpm Online Mapper: Well water was ft. --SE-after...... hours pumping gpm 6 Elevation:ft. Ground Level TOC Source: Land Survey GPS Topographic Map 2 Other -1 mile in. to ft. 7 WELL WATER TO BE USED AS: 5. Public Water Supply: well ID 10. Oil Field Water Supply: lease 1. Domestic: ☐ Household 6. Dewatering: how many wells? 11. Test Hole: well ID ☐ Cased ☐ Uncased ☐ Geotechnical 7. Aquifer Recharge: well ID ☐ Lawn & Garden 8. Monitoring: well ID 12. Geothermal: how many bores? ☐ Livestock 9. Environmental Remediation: well ID 2. Irrigation 3. Feedlot ☐ Air Sparge ☐ Soil Vapor Extraction b) Open Loop Surface Discharge Inj. of Water 13. Other (specify): 4. Industrial ☐ Recovery ☐ Injection Was a chemical/bacteriological sample submitted to KDHE? [Yes Mo If yes, date sample was submitted: Water well disinfected? ☑Yes ☐ No 8 TYPE OF CASING USED: Steel XPVC Other CASING JOINTS: MI Glued Clamped Welded Threaded Casing diameter 5 in to 100 ft, Diameter in to ft, Diameter in to ft. Diameter in to ft. Casing height above land surface 16 in Weight 160 lbs/ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: **™** PVC ☐ Other (Specify) Stainless Steel ☐ Fiberglass None used (open hole) □ Brass ☐ Galvanized Steel ☐ Concrete tile SCREEN OR PERFORATION OPENINGS ARE: GRAVEL PACK INTERVALS: From 44 ft. to 122 ft., From ft. to ft. Nearest source of possible contamination: ☐ Septic Tank ✓ Lateral Lines ☐ Pit Privy Livestock Pens ☐ Insecticide Storage Fuel Storage
Fertilizer Storage Cess Pool ☐ Sewer Lines Sewage Lagoon ☐ Abandoned Water Well Seepage Pit Feedyard ☐ Watertight Sewer Lines Oil Well/Gas Well Other (Specify)

Direction from well?

270

ft LITHOLOGIC LOG 10 FROM FROM LITHO. LOG (court.) or PLUGGING INTERVALS op. Soll ed - Shale Notes: INSTRUCTIONS: Send one copy to WATER WELL OWNER and retain one copy for your records. Submit fee of \$5.00 for each constructed well along with one (white) copy to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topolas, Kansas 66612-1367. Telephone (785) 296-3565. Visit us at http://www.kdhcks.gow/waterwell/index.html

KSA 82a-1212

State