

1 LOCATION OF WATER WELL: County: <u>Kingman</u>	Fraction <u>SE</u> $\frac{1}{4}$ <u>SE</u> $\frac{1}{4}$ <u>SW</u> $\frac{1}{4}$	Section Number <u>17</u>	Township Number T <u>18</u> S	Range Number R <u>7</u> <u>W</u>
---	---	-----------------------------	----------------------------------	-------------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1 mile south $\frac{1}{4}$ mile east of Kingman, Kans.

2 WATER WELL OWNER: <u>STEVE PARSONS</u>	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: <u>820 N. Spruce</u>	Application Number:
City, State, ZIP Code: <u>Kingman, Kans 67068</u>	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <u>66'</u> ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. <u>34'</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>30'</u> ft. below land surface measured on mo/day/yr <u>Feb. 28-96</u> Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>25</u> gpm; Well water was <u>NA</u> ft. after hours pumping gpm Bore Hole Diameter <u>7 7/8</u> in. to <u>66'</u> ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <u>X</u> No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued <u>X</u> Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<u>X</u> 2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter <u>5"</u> in. to <u>41'</u> ft., Dia	in. to ft., Dia	in. to ft.	Threaded
Casing height above land surface <u>15"</u> in., weight	<u>160</u> lbs./ft. Wall thickness or gauge No.	<u>SDR 26</u>	
TYPE OF SCREEN OR PERFORATION MATERIAL:	<u>XX</u> 7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
11 Other (specify)	12 None used (open hole)		
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	<u>XX</u> 8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <u>66'</u> ft. to <u>41'</u> ft., From ft. to ft.		
GRAVEL PACK INTERVALS:	From <u>66'</u> ft. to <u>40'</u> ft., From ft. to ft.		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<u>XX</u> 3 Bentonite	4 Other
Grout Intervals: From <u>40'</u> ft. to <u>36'</u> ft., From <u>23'</u> ft. to <u>3'</u> ft., From ft. to ft.				
What is the nearest source of possible contamination:	<u>XX</u> 0 Livestock pens	14 Abandoned water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	
Direction from well? <u>WEST</u>	How many feet? <u>App. 600'</u>			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	5'	Top soil.			
5'	11'	Clay.			
11'	21'	Brown sandy clay.			
21'	29'	Fine sand.			
29'	30'	clay.			
30'	42'	Medium Course sand.			
42'	46'	Clay.			
46'	52'	Medium course sand.			
52'	54'	Clay.			
54'	66'	Course sand.			
66'		Red Bed.			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>Feb. 23 - 1996</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>112</u> This Water Well Record was completed on (mo/day/yr) <u>Mar. 21 - 1996</u> under the business name of <u>Wells Drilling Co.</u> by (signature) <u>Dal Wells</u>
