

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Kingman		SE 1/4 SE 1/4 SE 1/4	16	T 28 S	R 7 E/W
Distance and direction from nearest town or city street address of well if located within city? 2 miles south, 1 3/4 miles east of Kingman, Kans					
2 WATER WELL OWNER: Jon Messenger					
RR#, St. Address, Box # : RT#1			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Kingman, Kans.			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 125' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 40' ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 34' ft. below land surface measured on mo/day/yr June 12-96 Pump test data: Well water was Na ft. after hours pumping gpm Est. Yield 5 gpm; Well water was ft. after hours pumping gpm Bore Hole Diameter 7 7/8" in. to 21' ft. and 6 3/4" in. to 125' ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
X2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	Welded
Blank casing diameter 5" in. to 21' ft. Dia		7 Fiberglass	Threaded		
Casing height above land surface 14" in., weight 160 lbs./ft. Wall thickness or gauge No. SDR26					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless steel	5 Fiberglass	8 RMP (SR)	11 Other (specify)
2 Brass		4 Galvanized steel	6 Concrete tile	9 ABS	12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:					
1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	XX1 None (open hole)
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
SCREEN-PERFORATED INTERVALS: From 999 ft. to 999 ft.		7 Torch cut 999 ft. to 999 ft.			
GRAVEL PACK INTERVALS: From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	XXX Bentonite	4 Other	
Grout Intervals: From 22 ft. to 2 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
XX1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
XX Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
Direction from well? South		How many feet? 200'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0'	21'	Top soil & Clay			
21'	40'	Red Bed.			
40'	41'	Broken red bed.			
41'	73'	Red Bed.			
73'	74'	Broken red bed.			
74'	125'	Red Bed.			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 12 1996 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 112 This Water Well Record was completed on (mo/day/yr) July 5 1996 under the business name of Wells Drilling Co. by (signature) [Signature]					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					