WATER WELL RECORD Form WWC-5 KSA 82a-1212 ID No. 0042507

1 LOCATION OF WATER WEL County: Kingman Distance and direction from near	L: Fraction		Section	n Number	Township Nur	nber l	Range Number
Distance and direction from near		NE ¼ NW	% Section		T 28		R 7 W
					, 20	<u> </u>	· , , , , , , , , , , , , , , , , , , ,
410 N. Main St., Kingman		areas or well in locates in	unit only .				
WATER WELL OWNER: A		al Remediation, L	_C				
R#, St. Address, Box # : 30					Board of Agricu	lture Division	of Water Resources
ity State ZIP Code M	alvern, PA 19355	5			Application Nur	nher:	
LOCATE WELL'S LOCATON	WITH				7 pprioditori i var		
LOCATE WELL'S LOCATON AN "X" IN SECTION BOX:	4 DEPTH OF C	COMPLETED WELL	25	ft. ELEV	ATION:	1509.42	2 (TOC)
†	Depth(s) Ground	water Encountered 1			4	11. 3 .	
NX NE -	WELL'S STATIC	WATER LEVEL 1	5.99 ft. be	elow TOC r	neasured on mo/da	y/yr	02/19/08
	Pum	p test data: Well water	was	ft	. after	hours pum	ping gpm
№ W	E Est. Yield	gpm: Well water	was	ft	. after	hours pum	ping gpm
ī l ! l !	Bore Hole Diame	eter 8.25 in. to TO BE USED AS: 5 Pu c 3 Feed lot 6 Oi	25		ft. and	in. to	ft
SW SE	WELL WATER 7	TO BE USED AS: 5 Pu	blic water sup	ply	8 Air condition	ing 11 lr	njection well
	1 Domestic	c 3 Feed lot 6 Oi	field water su	ipply	9 Dewatering	12 (other (Specify below)
S	2 Irrigation						
3	Was a chemical	/bacteriological sample s	ubmitted to De	epartment?	Yes No X	If yes, mo	o/day/yr sample was
	submitted			Wa	ter Well Disinfected	l? Yes	No X
TYPE OF BLANK CASING U	SED:	5 Wrought Iron	8 Concret	e tile	CASING JOIN	TS: Glued _	Clamped
1 Steel 3	RMP (SR)	6 Asbestos-Cement	9 Other (s	pecify belo	w)	Welded	
2 PVC 4	ABS	7 Fiberglass				Threaded	Flush
Name to a series of the series	9 15	E 6 B:			4 D:-	*	
Casing height above land surface	Flushmount	in unight	703	lbe /ft	Wall thickness or	rauge No	SCH. 40
Casing height above land surfac STATE OF SCREEN OR PERFORM	PATION MATERIAL	. III., Weight	7.700	DS./IL.	10 Ache	etoe-cement	
1 Steel 3	Stainless steel	5 Fiberalass	8 5	MP (SR)	11 Other	(enecify)	
2 Brass 4	Galvanized steel	5 Fiberglass6 Concrete tile	9 4	ABS	12 None	used (open I	hole)
SCREEN OR PERFORATION C		5 Gauze	ed wrapped		8 Saw cut	11	None (open hole)
1 Continuous slot	3 Mill slot				9 Drilled holes		
2 Louvered shutter		7 Torch	cut		10 Other (speci-	fy)	
SCREEN-PERFORATED INTER		15 ft. to	25	ft. F	rom	ft. to	f
		ft. to					
GRAVEL PACK INTERV	VALS: From	14 ft. to	25	ft. F	rom *	ft. to	f
		ft. to					f
6 GROUT MATERIAL: 1	Nest cement '	Cement grout	3 Bent	nnite	4 Other		
Grout Intervals From		π. From	π. το				ft. tof doned water well
What is the nearest source of po 1 Septic tank		7 Pit privy			tock pens storage	15 Oil we	
2 Sewer lines	4 Lateral lines				•		
3 Watertight sewer lines	6 Seepage pit				ticide storage	io Other	(opeony below)
Direction from well?	o Geepage pit	. a recuyar	•	How many	•		
Direction noin well:	DE LITHO	LOGIC LOG	FROM	TO		JGGING INTI	ERVALS
FROM TO COD	Clayey Sand, I						
FROM TO COD 0 25							
0 25							
			s (1) construc	ted, (2) rec	onstructed, or (3) pl	ugged under	my jurisdiction and w
0 25 7 CONTRACTOR'S OR LAND completed on (mo/day/yr)	03/	05/08	and thi	s record is	true to the best of r	ny knowledge	e and belief. Kansas
0 25	03/ 9 e No.		and thi	s record is	true to the best of r	ny knowledge	