WAILK WLL	L RECURD	FORM W	W C-3	וע		r Resources App. N	0.	
		Fraction					Range Number	
		NW ¼ NE ¼ NW			32	T 28 S		
Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here					Global Positioning System (GPS) information:  Latitude: 37.56695 (in decimal degrees)			
					Longitude: 098.11481 (in decimal degrees)			
From Kingman-4S to 40th 1/8W 1 3/4S ESR				Elevation: 1597				
RALPH HENNING TRUST					<u>Datum</u> : ☐ WGS 84, ☐ NAD 83, <b>[</b> NAD 27			
2 WATER WELL OWNER: Alvin & Sondra Henning				Collect	Collection Method:			
RR#, Street Address, Box #: 4216 SW 20 Avenue				GPS unit (Make/Model: Garmin csx Digital Map/Photo,  Topographic Map, Land Survey				
City, State, ZIP Code : Kingman, Kansas 67068				Est. Accuracy: $\boxed{<3 \text{ m}}$ , $\boxed{2}$ 3-5 m, $\boxed{5}$ 5-15 m, $\boxed{>}$ 15 m				
3 LOCATE WELL								
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 60 ft.								
SECTION BOX								
WELL 5 STATIC WATER ELVEL								
Pump test data: Well water was								
W  NW   -NE   EST. HELD							fi	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW SE	Domestic D Feedlet D Oil field water greatly D Davietaring D Other (See if the law)							
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well Stock								
Was a chemical/bacteriological sample submitted to Department?  Yes  No								
S If yes, mo/day/yr sample was submitted								
water went distincted? 12 Tes 140								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .5 in. to .40 ft., Diameter in. to								
Casing height above land surface16								
Steel Stainless Steel PVC Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot								
SCREEN-PERFORATED INTERVALS: From40								
From								
GRAVEL PACK INTERVALS: From80 ft. to18 ft., From ft. to ft.								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From .18								
What is the hearest source of possible contamination:   Septic tank								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
☐ Watertight sewer lines ☐ Seepage pit ☐ Feedyard ☐ Fertilizer storage ☐ Oil well/gas well								
	well						CCDIC DITERVAL	
FROM TO 0 2	LITHOLOG	IC LUG	FROM	TO	LITHO, LC	or PLU	GGING INTERVALS	
	Top soil Brown silty clay							
	Small sand							
	Official Safia							
Z CONTENT OF STATE	DIC OR LANDOWN	O CEDMIN COM	T 271					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was  constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 8-3-2011 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/year) 8-19-2011								
under the business name of Rosencrantz-Bemis Ent.  by (signature) Appear Deduced.								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.  Telephone 785-296-5522. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html.								
KSA 82a-1212 Check: ✓ White Copy, ☐ Blue Copy, ☐ Pink Copy								