1 LOCATION OF WATER WELL: Fraction  County: Kingman NE ¼ SW ¼ NW  Distance and direction from nearest town or city street address of wellocated within city? 75' E of 101 N Main Kingman KS  2 WATER WELL OWNER: ADM Collingwood Grain	if Global Positioning System (decimal degrees, min. of 4 dig. Latitude: N 37.64167°
Distance and direction from nearest town or city street address of wellocated within city? 75' E of 101 N Main Kingman KS  WATER WELLOWNER: ADM Collingwood Grain	if Global Positioning System (decimal degrees, min. of 4 digital Latitude: N 37.64167°
2 WATER WELL OWNER: ADM Collingwood Grain	Longitude: W 98.11303°
RR#, St. Address, Box # : 1700 N. Halsted	Elevation: RIM: 1504.35; TOC: 1504.14  Datum: WGS84  Data Collection Method: legal survey
City, State, ZIP Code : Hutchinson KS 67502	
3 LOCATE WELL'S 4 DEPTH OF COMPLETED WELL 1	MW12.
LOCATON  NATION AND AND AND AND AND AND AND AND AND AN	ft 2 ft. 3
N Pump test data: Well water was	ft. after hours pumping gr
Fet Vield gnm: Well water was	ft. after hours pumping gr ft. after hours pumpi
NW NE WELL WATER TO BE USED AS: 3 Full Name of the Nam	supply 9 Dewatering 12 Other (Specify belo
2 Irrigation 4 Industrial 7 Domestic (la	n & garden) (10) Wonton ing wen
Sample was submitted	water Well Disinfected? Yes No X ; If yes, mo/day/y
5 TYPE OF CASING USED: 5 Wrought Iron 8 C	oncrete tile CASING JOINTS: Glued Clamped
DVC 4 ARS 7 Fiberglass	Threaded X
Plank agging digmeter 2 in to 4.57 ft., Dia	in. to ft., Dia in. to
Cooling height below land surface 0.21 ft Weight	lbs./ft. Wall thickness or gauge No.
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 (2) PVC 4 ABS 7 Fiberglass  Blank casing diameter 2 in. to 4.57 ft., Dia  Casing height below land surface 0.21 ft., Weight  TYPE OF SCREEN OR PERFORATION MATERIAL:  1 Steel 3 Stainless steel 5 Fiberglass 7 PVC  2 Brass 4 Galvanized steel 6 Concrete tile 8 RM (SR)  SCREEN OR PERFORATION OPENINGS ARE:	10 Asbestos-Cement 12 None used (open note)
SCREEN OR PERFORATION OPENINGS ARE:  1 Continuous slot 3 Mill slot 5 Gauze wrapped 2 Louvered shutter 4 Key punched 6 Wire wrapped SCREEN-PERFORATED INTERVALS: From 4.57 ft From ft GRAVEL PACK INTERVALS: From 3 ft From ft	Torch cut 9 Drilled holes 11 None (open hole) Saw Cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 4.57 ft	to 19.57 II. From II. W
From	to II. From It to
GRAVEL PACK INTERVALS: From 3 II	to ft From ft to
From	10 110m
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (	Bentonite 4 Other Concrete: 0-1
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout (Grout Intervals From 1 ft. to 3 ft. From What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10	
2 Sewer lines 5 Cess pool 8 Sewage lagoon (11) 3 Waterright sewer lines 6 Seepage pit 9 Feedyard 12	uel storage 14 Abandoned water well below) ertilizer storage 15 Oil well/ gas well many feet? ~210'
	ROM TO PLUGGING INTERVALS
FROM TO LITHOLOGIC LOG  0 4 Grass on top; Brown silty clay	
4 19.75 Medium tan sand	
	Flushmount waiver from BOW
	Flushmount waiver from BOW
and or the business name of Larsen & Associates, Inc.	well Record was completed on (morday/year) 3/19/14 (signature)
under the business name of Francei of Transcription	copies to Kansas Departmen of Health and Environment, Bureau of Wate phone 785-296-5522. Send on the WATER WELL OWNER and retain or cov/waterwell.