

MW-4 2211093

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Kingman	SE 1/4 NW 1/4 SW 1/4	5	T 28 S	R 7 E

Distance and direction from nearest town or city street address of well if located within city?
229 S. Main, Kingman 6'E 45'S. of N.E. cor. of Warehouse

2 WATER WELL OWNER: Langley Oil & Gas, Inc.	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: 229 S. Main	Application Number:
City, State, ZIP Code: Kingman, KS 67608	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 12.5 ft. ELEVATION:
	Depth(s) Groundwater Encountered: 1.75 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 5.82 ft. below land surface measured on mo/day/yr 2-17-95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter: 2 in. to ft. Dia			Threaded Flush
Casing height above land surface: Flush in. weight 7.03 lbs./ft. Wall thickness or gauge No. 154			
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:			
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
SCREEN-PERFORATED INTERVALS:			
From: 2.5 ft. to 12.5 ft.			
GRAVEL PACK INTERVALS:			
From: 2.5 ft. to 12.5 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 2.5 ft. to 0.5 ft.				
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	16 Other (specify below)
Direction from well? S.S.W				
				How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0.0	2.5	Fill, sandy			
2.5	3.5	Concrete			
3.5	7.5	Sand m.c. grain, silty, sl. clayey			
7.5	12.5	Sand c.v.c. grain, silty			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-17-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 531 This Water Well Record was completed on (mo/day/yr) 2-17-95 under the business name of GSI by (signature) Bryce Clements
