

KOH

WATER WELL RECORD

Form WWC-5

KSA 82a-1212

ID No.

1	LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County:	Kingman	BE 1/4 SE 1/4 SE 1/4	39	T 28 S	R 9 E

Distance and direction from nearest town or city street address of well if located within city?


6.5 mi. S of Hwy on 90 Ave West Side of Rd

2 WATER WELL OWNER: Cairo Coop - Calista Location

RR#, St. Address, Box # :  
City, State, ZIP Code :

NA

Board of Agriculture, Division of Water Resources  
Application Number:

3	LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4	DEPTH OF COMPLETED WELL 95 ft. ELEVATION: NA
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft.	
		WELL'S STATIC WATER LEVEL 54 ft. below land surface measured on mo/day/yr	
		Pump test data: Well water was ft. after hours pumping gpm	
		Est. Yield gpm: Well water was ft. after hours pumping gpm	
		WELL WATER TO BE USED AS:	
		5 Public water supply 8 Air conditioning 11 Injection well	
		X 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)	
		2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well	
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No	

5	TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
	1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
	2 PVC	4 ABS	7 Fiberglass	Welded
				Threaded
Blank casing diameter 5 in. to 95 ft. Dia 12 in. to 160 ft. Dia				
Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No.				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel		3 Stainless Steel	5 Fiberglass	7 PVC X
2 Brass		4 Galvanized Steel	6 Concrete tile	8 RMP (SR)
				9 ABS
				10 Asbestos-Cement
				11 Other (Specify)
				12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE:		5 Guazed wrapped		8 Saw cut
X Continuous slot		3 Mill slot		9 Drilled holes
2 Louvered shutter		4 Key punched		10 Other (specify)
				11 None (open hole)
SCREEN-PERFORATED INTERVALS:		From 95 ft. to 75 ft.		
		From 75 ft. to 25 ft.		
GRAVEL PACK INTERVALS:		From 95 ft. to 25 ft.		
		From 25 ft. to ft.		

6	GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 25 ft. to 4 ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
				Nothing on location	
Direction from well?		How many feet?			

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	6	BLACK top So.			
6	16	Tan Clay			
16	30	White Clay			
30	36	Fine Sand			
36	55	White Clay			
55	66	Tan clay			
66	80	Fine Sand			
80	90	Coarse Sand			
90	92	Tan clay			
92	95	Red Shale			

7	CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-10-95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No 672 This Water Well Record was completed on (mo/day/yr) 8-17-95 under the business name of CROWD'S WATER WELL by (signature) [Signature]
---	---

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well.