

1 LOCATION OF WATER WELL: Sedgwick	FRACTION SW 1/4 SE 1/4 NW 1/4	Section Number 23	Township Number T 29 S	Range Number R 1W E/W
--	---	-----------------------------	----------------------------------	---------------------------------

Distance and direction from nearest town or city street address of well if located within city?


9952 S. 51st St. West Clearwater, KansasWATER WELL OWNER: **FRIESEN, Jim**RR#, ST. ADDRESS, BOX #: **9952 S. 51st St. West**

Board of Agriculture, Division of Water Resource

CITY, STATE, ZIP CODE: **Clearwater, Kansas**

Application Number:

LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:



4 DEPTH OF COMPLETED WELL	55	ft.	ELEVATION:	
Depth(s) groundwater Encountered	1	ft.		
WELL'S STATIC WATER LEVEL	30	FT. BELOW LAND SURFACE MEASURED ON	09/10/1997	
Pump test data:	Well water was	ft.	after	hours pumping
Est. Yield	gpm:	Well water was	ft.	after
Bore Hole Diameter	12	in.	to 55	ft.
WELL WATER TO BE USED AS:	5 Public water supply	8 Air conditioning	11 Injection well	
1 Domestic	3 Feedlot	6 Oil field water supply	9 Dewatering	12 Other (Specify below)
2 Irrigation	4 Industrial	7 Lawn and garden only	10 Monitoring well	
Was a chemical/bacteriological sample submitted to Department? Yes	No ☒	If yes, mo/day/yr sample was		
submitted	Water Well Disinfected? Yes ☒	No		

5 TYPE OF CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS:	Glued ☒	Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (Specify below)	Welded	
2 PVC	4 ABS	7 Fiberglass	SDR-26	Threaded	
Blank casing Diameter	5	in.	to 35	ft.	
Casing height above land surface	12	in.	weight 2.35	lbs. / ft.	Wall thickness or gauge No. .214
TYPE OF SCREEN OR PERFORATION MATERIAL:	5 Fiberglass	8 RMP (SR)	10 Asbestos-cement	11 other (specify)	
1 Steel	3 Stainless Steel	6 Concrete tile	9 ABS	12 None used (open hole)	
2 Brass	4 Galvanized steel	5 Gauzed wrapped	8 Saw cut	11 None (open hole)	
SCREEN OR PERFORATION OPENING ARE:	6 Wire wrapped	9 Drilled holes	10 Other (specify)		
1 Continuous slot	3 Mill slot	7 Torch cut			
2 Louvered shutter	4 Key punched				
SCREEN-PERFORATION INTERVALS:	from 35	ft. to 55	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.
GRAVEL PACK INTERVALS:	from 24	ft. to 55	ft., From	ft. to	ft.
	from	ft. to	ft., From	ft. to	ft.

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 4	ft. to 24	ft. From	ft. to	ft. From
What is the nearest source of possible contamination:	10 Livestock pens	14 Abandon water well		
1 Septic tank	4 Lateral lines	7 Pit privy	11 Fuel storage	15 Oil well/Gas well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	12 Fertilizer storage	16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	13 Insecticide storage	None Apparent

Direction from well?	How many feet?
FROM	TO
0	2
2	15
15	30
30	33
33	42
42	55
LITHOLOGIC LOG	PLUGGING INTERVALS
topsoil	
clay	
fine sand	
clay	
medium to coarse sand	
blue shale	

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 09/10/1997 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 09/12/97 Under the business name of Harp Well & Pump Service, Inc. by (signature)
--

Todd S. Harp