

1 LOCATION OF WATER WELL:	FRACTION	Section Number	Township Number	Range Number	
Sedgwick	NW 1/4 NE 1/4 SE 1/4	6	T 29 S	R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city?					
1/2 m. S. of 71st S. and 1/4 W. of Maize Road Wichita, Kansas					
WATER WELL OWNER: GIDEON, Terry					
RR#, ST. ADDRESS, BOX #: 10622 Bluewater					
CITY, STATE, ZIP CODE: Clearwater, Kansas					
Board of Agriculture, Division of Water Resource					
Application Number:					
LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL 45 ft. ELEVATION:				
	Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.				
	WELL'S STATIC WATER LEVEL 10 FT. BELOW LAND SURFACE MEASURED ON 07/09/1999				
	Pump test data: Well water was 1 ft. after 2 hours pumping 3 gpm				
	Est. Yield 12 gpm: Well water was 1 ft. after 2 hours pumping 3 gpm				
	Bore Hole Diameter 12 in. to 45 ft. and 1 in. to 1 ft.				
WELL WATER TO BE USED AS:					
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well 12 Other (Specify below)					
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (Specify below) Welded 7 Fiberglass SDR-26 Threaded					
Blank casing Diameter 5 in. to 30 ft., Dia in. to ft., Dia in. to ft.					
Casing height above land surface 12 in., weight 2.35 lbs. / ft. Wall thickness or gauge No. .214					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENING ARE:					
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATION INTERVALS: from 30 ft. to 45 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: from 26 ft. to 45 ft., From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other bentonite hole plug					
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From 24 ft. to 26 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent					
Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	topsoil			
3	9	fine sand			
9	17	clay			
17	27	fine sand			
27	40	medium sand			
40	45	grey shale			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 07/09/1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 07/12/99 Under the business name of Harp Well & Pump Service, Inc. by (signature) Todd S. Harp					