

1) LOCATION OF WATER WELL: County: <u>Sedgewick</u>		Fraction <u>SE 1/4 SE 1/4 SW 1/4</u>	Section Number <u>24</u>	Township Number T <u>29</u> S	Range Number R <u>1</u> E <u>W</u>
Distance and direction from nearest town or city street address of well if located within city? <u>2 miles south of Haysville, 2 1/2 miles West on 103rd South</u>					
2) WATER WELL OWNER: RR#, St. Address, Box # City, State, ZIP Code		Board of Agriculture, Division of Water Resources Application Number:			
3) LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4) DEPTH OF COMPLETED WELL: <u>65</u> ft. ELEVATION: Depth(s) Groundwater Encountered 1. <u>11</u> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <u>28</u> ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield <u>25</u> gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <u>8</u> in. to ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 2 Irrigation 3 Feedlot 4 Industrial 5 Public water supply 6 Oil field water supply 7 Lawn and garden only 8 Air conditioning 9 Dewatering 10 Monitoring well 11 Injection well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5) TYPE OF BLANK CASING USED: 1 Steel 2 PVC 3 RMP (SR) 4 ABS Blank casing diameter 5 in. to 45 ft. Dia 12 in. to ft. Dia 12 in. to ft. Dia Casing height above land surface 12 in. weight lbs./ft. Wall thickness or gauge No. <u>SDR26</u>		CASING JOINTS: Glued Clamped Welded Threaded 5 Wrought iron 6 Asbestos-Cement 7 Fiberglass 8 Concrete tile 9 Other (specify below) TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 2 Brass 3 Stainless steel 4 Galvanized steel 5 Fiberglass 6 Concrete tile 7 PVC 8 RMP (SR) 9 ABS 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Louvered shutter 3 Mill slot 4 Key punched 5 Gauzed wrapped 6 Wire wrapped 7 Torch cut 8 Saw cut 9 Drilled holes 10 Other (specify) 11 None (open hole) SCREEN-PERFORATED INTERVALS: From 45 ft. to 65 ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 22 ft. to 65 ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6) GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 2 Sewer lines 3 Watertight sewer lines 4 Lateral lines 5 Cess pool 6 Seepage pit 7 Pit privy 8 Sewage lagoon 9 Feedyard 10 Livestock pens 11 Fuel storage 12 Fertilizer storage 13 Insecticide storage 14 Abandoned water well 15 Oil well/Gas well 16 Other (specify below) Direction from well? <u>SE</u> How many feet? <u>75</u>					
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS					
0	3	Top Soil			
3	11	Gray Shale			
11	60	Sand			
60	65	Shale			
7) CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>7-9-99</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>464</u> This Water Well Record was completed on (mo/day/yr) <u>7-12-99</u> under the business name of <u>Water Well Services</u> by (signature) <u>[Signature]</u>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					