


WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL: Sedgwick		FRACTION NW 1/4 NW 1/4 SW 1/4		SECTION NUMBER 3	TOWNSHIP NUMBER T 29 S	RANGE NUMBER R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 7620 S. Ridge Road Haysville, Kansas						
2 WATER WELL OWNER: TIBITS, A.		Board of Agriculture, Division of Water Resource				
RR#,ST. ADDRESS,BOX #: 7620 S. Ridge Road		Application Number:				
CITY, STATE: Haysville, Kansas		ZIP CODE:				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 97 ft. ELEVATION:				
		Depth of groundwater Encountered: ft.				
		WELL'S STATIC WATER LEVEL 30 FT. BELOW LAND SURFACE MEASURED ON 6/20/08				
		Pump test data: Well water was ft. after hours of pumping @ gpm				
		Est. Yield: gpm Well water was ft. after hours of pumping @ gpm				
		Bore Hole Diameter 12 in. to 97 ft. and in. to ft.				
		WELL WATER TO BE USED AS:				
		1. Domestic 3. Feedlot 5. Public water supply 7. Lawn and garden only 9. Dewatering 11. Injection well				
		2. Irrigation 4. Industrial 6. Oil field water supply 8. Air conditioning 10. Monitoring well 12. Other (Specify below)				
		Was a chemical/bacteriological sample submitted to Department? YES NO ; If yes, what mo/day/yr was sample submitted				
		Was Water Well Disinfected? YES NO				
5 TYPE OF CASING USED:		CASING JOINTS: Glued Threaded				
1. Steel 3. RPM (SR) 5. Wrought Iron 7. Fiberglass 9. Other (Specify below)		Welded Clamped				
2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete tile SDR-26						
Blank casing diameter 5 in. to 77 ft., Dia. in. to ft., Dia. in. to ft.						
Casing height above land surface: 12 in., Weight: 2.35 lbs. / ft. Wall thickness or gauge No. .214						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)						
2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) 10. Asbestos-Cement 12. None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1. Continuous slot 3. Mill slot 5. Gauzed wrapped 7. Torch cut 9. Drilled holes 11. None (open hole)						
2. Louvered shutter 4. Key punched 6. Wire wrapped 8. Saw cut 10. Other (specify)						
SCREEN - PERFORATION INTERVAL		From 77 ft. to 97 ft., From ft. to ft., From ft. to ft.				
GRAVEL PACK INTERVALS:		From 24 ft. to 97 ft., From ft. to ft., From ft. to ft.				
6 GROUT MATERIALS:		Other bentonite hole plug				
1. Neat cement 2. Cement Grout 3. Bentonite						
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1. Septic tank 4. Lateral lines 7. Pit privy 10. Livestock pens 13. Insecticide storage 15. Oil well/Gas well						
2. Sewer lines 5. Cess Pool 8. Sewage lagoon 11. Fuel storage 14. Abandon water well 16. Other (specify below)						
3. Watertight sewer line 6. Seepage pit 9. Feed yard 12. Fertilizer storage						
Direction from well? South		How many feet? 100 ft. plus				
From To LITHOLOGIC LOG		From To LITHOLOGIC LOG				
0	4	topsoil				
4	15	clay				
15	20	fine sand				
20	35	clay				
35	50	medium sand				
50	75	clay				
75	95	medium sand				
95	97	shale				
7 Contractor's or Landowner's Certification: This water well was 1. constructed 2. reconstructed or 3. plugged under my jurisdiction and was completed on (mo/day/year) 6/20/2008 and this record is true to the best of my knowledge and belief.						
Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 6/23/2008						
under the business name of Harp Well and Pump Service by (signature) Todd S. Harp						