	WELL RE		Form W				vision of Wate	1/10/735	Well ID West
		Correction ATER WEI	☐ Change	Fraction		7.	ction Numb	r	ber Range Number
i .	y: Sedgwick	AIER WEI	uli.	4 NE 4	NW ¼		13	T 29 S	R 1 DE W
2 WELL OWNER: Last Name: First: Street or Rural Address where well is located (if unknown direction from nearest town or intersection): If at owner's address, Approximately 2 miles south and 2 miles west of Haysville Address:									(if unknown, distance and ner's address, check here:
City:		Tomas (distance)	State: KS		L				
WITH "	X" IN			LETED WI incountered: 1		71 f		ude: 37.533835 tude: -97.375131	(decimal degrees) (decimal degrees)
NW-	2) ft. 3) ft., or 4) WELL'S STATIC WATER LEVEL: 31 Well's STATIC water Level: 31 below land surface, measured on (mo-day above land surface, measured on (mo-day above land surface)					☐ Dry Well 40 ftyr) 12-04-19 ft. gpm ft. gpm ft. gpm		ontal Datum. □ WGS 84 □ NAD 83 ☑ NAD 27 e for Latitude/Longitude: GPS (unit make/model: (WAAS enabled? ☑ Yes □ No) and Survey □ Topographic Map Online Mapper:	
<u> </u>	S	Estimated Bore Hole		gpm 24 in. to	71	ft. and		e: Land Survey	t. Ground Level TOC GPS Topographic Map
1 mile in. to ft.									
1. Domestic	: chold & Garden cock ion ot	5. [6. [7. [8. [9. E	Dewatering Aquifer Red Monitoring	Remediation	vells? D : well ID Vapor E	xtraction	11. Test C 12. Georgia (2) C b) O	il Field Water Supply: Hole: well ID ased	Geotechnical
Was a chemical/bacteriological sample submitted to KDHE? ☐ Yes ☒ No If yes, date sample was submitted:									
Water well disinfected? Yes □ No 8 TYPE OF CASING USED: □ Steel ▼ PVC CASING JOINTS: ▼ Glued □ Clamped □ Welded □ Threaded □ Other									
8 TYPE OF CASING USED: Steel PVC CASING JOINTS: Glued Clamped Welded Threaded Other Casing diameter 12 in. to 52 ft., Diameter in. to ft., Diameter in. to ft. Casing height above land surface 12 in. Weight 12.71 lbs./ft. Wall thickness or gauge No490 TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Stainless Steel Fiberglass PVC Other (Specify) Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Louvered Shutter Key Punched Wire Wrapped Screen-Perforated Intervals: From 52 ft. to 70 ft., From ft. to ft., From ft. to ft. GRAVEL PACK INTERVALS: From 25 ft. to 71 ft., From ft. to ft., From ft. to ft.									
9 GROUT MATERIAL:									
Grout Intervals: From 0 ft. to 25 ft., From ft. to ft. Nearest source of possible contamination: Septic Tank Lateral Lines Pit Privy Livestock Pens Insecticide Storage Sewer Lines Seepage Pit Seepage Pit Feedyard Fertilizer Storage Oil Well/Gas Well Other (Specify) None Known Direction from well?									
10 FROM	ТО		LITHOLOG	IC LOG		FROM	TO	LITHO. LOG (cont.)	or PLUGGING INTERVALS
3	t	Topsoil Clay, brown							
15	+	Sand & gravel, f	ine to medium						
47	1	Clay, tan	to mediani						
53	70 9	Sand & gravel, f	ine to medium						
70	71	Weathered Shale	;						
Notes: 11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, or plugged under my jurisdiction and was completed on (mo-day-year) 12-04-19 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 185 This Water Well Record was completed on (mo-day-year) 12-09-19 under the business name of Clarke Well & Equipment, Inc.									
Mail	1 white copy al	long with a fee o	f \$5.00 for each	constructed we		sas Departmen	of Health and	Environment, Bureau of V	
1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Mail one to Water Well Owner and retain one for your records. Telephone 785-296-5524. Visit us at http://www.kdheks.izov/waterwell/index.html KSA 82a-1212 Revised 7/10/2015									