

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: SEDGWICK		NE 1/4 NE 1/4 NW 1/4		3		T 29 S		R 1 W	
Distance and direction from nearest town or city street address of well if located within city? 71st. ST. SOUTH, WICHITA, KS.									
2 WATER WELL OWNER: KANSAS CITY TESTING LAB.									
RR#, St. Address, Box # : P.O. BOX 6323									
City, State, ZIP Code : SHAWNEE MISSION, KS. 66206									
Board of Agriculture, Division of Water Resources Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 54 ft. ELEVATION: 42 ft.							
		Depth(s) Groundwater Encountered 1. 42 ft. 2. 42 ft. 3. 42 ft.							
		WELL'S STATIC WATER LEVEL 42 ft. below land surface measured on mo/day/yr							
		Pump test data: Well water was 42 ft. after 42 hours pumping 42 gpm							
		Est. Yield 42 gpm: Well water was 42 ft. after 42 hours pumping 42 gpm							
		Bore Hole Diameter 9 in. to 54 ft., and 54 in. to 54 ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial Lawn and garden only 10 Observation well							
Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
7 Fiberglass Threaded									
Blank casing diameter 6 in. to 44 ft., Dia 44 in. to 44 ft., Dia 44 in. to 44 ft.									
Casing height above land surface 12 in., weight 12 lbs./ft. Wall thickness or gauge No. SEA 4D									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass PVC 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify)									
9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 54 ft. to 44 ft., From 44 ft. to 44 ft., From 44 ft. to 44 ft.									
GRAVEL PACK INTERVALS: From 54 ft. to 44 ft., From 44 ft. to 44 ft., From 44 ft. to 44 ft.									
6 GROUT MATERIAL: Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 41 ft. to 42 ft., From 0 ft. to 41 ft., From 41 ft. to 41 ft.									
What is the nearest source of possible contamination: BENTONITE CEMENT Livestock pens 14 Abandoned water well									
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? How many feet?									
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG				
0	30	SAND							
30	40	CLAY w/SOME SAND							
40	54	SAND							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-6-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 138 This Water Well Record was completed on (mo/day/yr) 1-18-84 under the business name of KANSAS CITY TESTING LAB by (signature) Kenneth J. Rydman									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									