

1 LOCATION OF WATER WELL: County: SEDGWICK Fraction: NE 1/4 NE 1/4 NW 1/4 Section Number: 3 Township Number: T 29 S Range Number: R 1 NW

Distance and direction from nearest town or city street address of well if located within city? 71st ST. SOUTH, WICHITA, KS.

2 WATER WELL OWNER: KANSAS CITY TESTING LAB. P.O. BOX 6323 SHAWNEE MISSION, KS. 66206 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram showing a 36-acre section divided into four 9-acre quadrants (NW, NE, SW, SE). An 'X' is marked in the NW quadrant. A north arrow points upwards. A scale bar indicates 1 mile. The section is labeled with 'N', 'S', 'E', and 'W' on the sides.]

4 DEPTH OF COMPLETED WELL: 113 ft. ELEVATION: 1184.9 ft. Depth(s) Groundwater Encountered: 1. 42 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 10 in. to 113 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) CASING JOINTS: Glued Clamped 2 PVC 4 ABS 7 Fiberglass Welded Threaded Blank casing diameter: 4 in. to 113 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 24 in. weight lbs./ft. Wall thickness or gauge No. Sch. 40 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 2 Mill slot 3 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut SCREEN-PERFORATED INTERVALS: From 113 ft. to 80 ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From 113 ft. to 79 ft. From ft. to ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 77 ft. to 79 ft. From 0 ft. to 77 ft. From ft. to ft. What is the nearest source of possible contamination: BENTONITE CEMENT 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	10	CLAY			
10	30	SAND			
30	32.5	CLAY			
32.5	39.5	SILT			
39.5	62	SAND			
62	77.5	CLAY			
77.5	108	CLAYEY SAND / SANDY CLAY			
108	111	GRAVEL w/ SOME CLAY			
111	113	SHALE			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-4-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 438 This Water Well Record was completed on (mo/day/yr) 1-18-84 under the business name of KANSAS CITY TESTING LAB by (signature) Kenneth J. Rappaport

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.