

1 LOCATION OF WATER WELL: County: Sedgwick		Fraction SW 1/4 NW 1/4 SE 1/4	Section Number 4	Township Number T 29 S	Range Number R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 3/4 mile South of 71st St. So., 1/2 West of Ridge Rd. Wichita, Ks.					
2 WATER WELL OWNER: Bob Ulrich RR#, St. Address, Box # : 7700 Duis City, State, ZIP Code : Wichita, Ks.					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 17 ft. 2. 12-28-89 ft. 3. 12-28-89 ft. WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr Pump test data: Well water was 11 ft. after 12-28-89 hours pumping 12-28-89 gpm Est. Yield 11 gpm: Well water was 11 ft. after 12-28-89 hours pumping 12-28-89 gpm Bore Hole Diameter 11 in. to 11 ft., and 11 in. to 11 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 160 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 85 ft., Dia 5 in. to 85 ft., Dia 5 in. to 85 ft. Casing height above land surface 12 in., weight 2.29 lbs./ft. Wall thickness or gauge No. 214 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 160 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 3 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 85 ft. to 110 ft., From 85 ft. to 110 ft., From 85 ft. to 110 ft. GRAVEL PACK INTERVALS: From 24 ft. to 110 ft., From 24 ft. to 110 ft., From 24 ft. to 110 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 4 ft. to 24 ft., From 24 ft. to 110 ft., From 24 ft. to 110 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? How many feet? 13 Insecticide storage None apparent					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12-28-89 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 5-1-90 under the business name of Harp Well and Pump Service, Inc. by (signature) Mary Arnold					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320. Telephone: 913-296-5514. Send one to WATER WELL OWNER and retain one for your records.					