1 LOCATION OF WATER WELL:	FRACTION	Water Well Recor	d Form WWC-5	KSA 82a-1212 Section Number	Township Number	Range Number	
		NW 1/4 NW 1/4 NE 1			·	127	
Sedgwick		····	NE 1/4	8	T 29 s	R 1W E/W	
Distance and direction frem nearest town or ci	•	•		_			
9553 W. 79th S.		<u>& Tyler,</u>	<u>1/4 We</u>	st, then	<u>1/8 S.) Wichi</u>	ta,Kansas	
	TE, Alicia						
RR#, ST. ADRESS, BOX#: 1832 S. Spruce Board of Agriculture, Divivsion of Water Resource							
CITY, STATE, ZIP CODE: Wic	<u>hita, Kansa</u>	S			Application Number	F:	
JOCATE WELL'S LOCATION WITH	4 DEPTH OF COM		75	ft. ELE	VATION:		
N N	Depth(s) groundwa	ater Encountered	1	ft.	2 ft.	3 ft.	
	WELL'S STATIC WA	ATER LEVEL 2	5 FT	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	06/14/1993	
NWNE	Pump test	data: Well	water was	ft. a	ofter hours pum	nping gpm	
	Est. Yield	gpm: Well	water was	ft.	after hours pum	nping gpm	
₩ W E	Bore Hole Diameter	12 in.	to 75	ft.,	and in.	to ft.	
= "	WELL WATER TO B	BE USED AS:	5 Public wate	r supply {	B Air conditioning 11 1	injection well	
	1 Domestic	3 Feedlot	6 Oil field wa	ter supply	Dewatering 12 (Other (Specify below)	
3" 3"	2 Irrigation	4 Industrial	7 Lawn and g	arden oniy 1	0 Monitoring well		
Was a chemical/bacteriological sample submitted to Department? Yes No ✗; If yes, mo/day/yr sample was							
S submitted Water Well Disinfected? Yes X No							
5 TYPE OF CASING USED:		5 Wrought iron	9	Concrete tile	CASING JOINTS: (Blued X Clamped	
1 Steel 3 RMP (SR)		6 Asbestos-Cement		Other (Specify be	•	Welded	
2 PVC 4 ABS		7 Fiberglass	-	DR-26	,	Threaded	
Blank casing Diameter 5	in. to 5 5	ft., Dia	in.	to	ft., Dia in.	to ft.	
Casing height above land surface		m., Dia weight 2			Wall thickness or gauge No.	.214	
TYPE OF SCREEN OR PERFORA		weight 2		PVC	10 Asbestos-cem		
1 Steel 3 Stainless Steel		5 Flberglass		RMP (SR)	11 other (specify	v)	
2 Brass 4 Galvanized ste		6 Concrete tile	9	ABS	12 None used (o		
		E Can	hongrows box		8 Saw cut	11 None (open hole)	
SCREEN OR PERFORATION OPENING ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open 11 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes						` ' '	
To College Court C							
Totaled							
SCREEN-PERFORATION INTER	55		t. to 75	ft., From	ft. to	ft.	
from		=:	t. to	ft., From		ft.	
GRAVEL PACK INTER		-	it. to 75	ft., From		ft.	
CONTRACTOR AND	from 2 C		t. to	ft., From ntonite	ft. to	n.	
0		ement grout					
Grout Intervals: From 4	ft. to 24	ft., From	ft.	to 10 Livestoe	ft., From	ft. to ft.	
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines		7 Pit privy		11 Fuel sto		Abandon water well	
		• •			13	15 Oil weil/Gas well	
2 Sewer lines 5 Cess pool		8 Sewage lagoon			44	16 Other (specify below)	
3 waterught sewer lines 6 Seepage pit 9 reedyard None Apparent						Apparent	
Direction from well?	TIMILOT COTOT CO				How many feet?	DVATC	
FROM TO	LITHOLOGIC LOG		FROM	TO	PLUGGING INTE	KVALS	
0 2 topsoil							
2 45 clay				+			
45 50 fine sa	na			 			
50 55 clay	-						
55 75 medium	to coarse s	and					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and							
was completed on (mo/day/year)							
Well Contractor's License No	<u> 236 </u>	This Water Well F	Record was o	ompleted on (me	o/day/yr}Ω. 6./.2	8/93	
Under the business name of Harp Well & Pump Service, Inc. by (signature)							
580 Under the business name of MALL MALL MALL MALL MALL MALL MALL MAL							
1 300					U *		