

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: SEDGWICK		NE ¼ SE ¼ SE ¼		11		T 29 S		R 1W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
1/2 mile N. of 87th St. S., 1 blk. W. of West St., Haysville, Ks.									
2 WATER WELL OWNER: Grover White									
RR#, St. Address, Box # : 402 Linden Lane									
City, State, ZIP Code : Haysville, Ks.									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 70 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 30 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 5/2/81							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 11 in. to ft., and in. to ft.							
		WELL WATER TO BE USED AS:							
		1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Cer-Mac Welded 7 Fiberglass SDR-26 Styrene Threaded									
Blank casing diameter 5 in. to 50 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 203									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement Same 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) SDR-26 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut .06 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 50 ft. to 70 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 14 ft. to 70 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 40" ft. to 14 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) NONE APPARENT									
Direction from well? How many feet?									
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG				
0	3	Topsoil							
3	11	Clay							
11	27	Medium Sand							
27	35	Clay							
35	50	Fine Sand							
50	70	Medium Sand							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5/2/81 and this record is true to the best of my knowledge and belief. Kansas									
Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 7-6-81									
under the business name of Harp Well & Pump Serv., Inc. by (signature) m. Arnold									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									