

1 LOCATION OF WATER WELL:		Fraction		Township Number		Range Number	
County: Sedgwick		NW 1/4 NW 1/4 NE 1/4		13		T 29 S R 1 EW	
Distance and direction from nearest town or city street address of well if located within city?							
25 3/8 W OF WEST EDGE OF HAYSVILLE, KS							
2 WATER WELL OWNER: Slawson Drilling Company				Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #: Great Bend, Kansas				Application Number:			
City, State, ZIP Code:				Lease: Love D-4			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 60 ft. ELEVATION:					
		Depth(s) Groundwater Encountered 1. 36 ft. 2. ft. 3. ft.					
		WELL'S STATIC WATER LEVEL 36 ft. below land surface measured on mo/day/yr 8 Nov. 83					
		Pump test data: Well water was ft. after hours pumping gpm					
		Est. Yield 80 gpm: Well water was ft. after hours pumping gpm					
		Bore Hole Diameter 10 in. to 60 ft. and in. to ft.					
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well					
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)					
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well					
		Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted					
		Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped							
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded							
7 Fiberglass Threaded							
Blank casing diameter 5 in. to 40 ft. Dia. in. to ft. Dia. in. to ft.							
Casing height above land surface 12 in., weight lbs./ft. Wall thickness or gauge No. 214							
TYPE OF SCREEN OR PERFORATION MATERIAL:							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement							
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)							
12 None used (open hole)							
SCREEN OR PERFORATION OPENINGS ARE:							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes							
7 Torch cut 10 Other (specify)							
SCREEN-PERFORATED INTERVALS: From 40 ft. to 60 ft. From ft. to ft.							
GRAVEL PACK INTERVALS: From 10 ft. to 60 ft. From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other							
Grout Intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.							
What is the nearest source of possible contamination:							
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well							
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well							
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)							
13 Insecticide storage NONE							
Direction from well? How many feet?							
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG							
0 2 Soil, top							
2 8 Clay, tan							
8 25 Sand, fine to coarse							
25 34 Clay, blue'							
34 60 Sand, fine to coarse and fine to med gravel							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8 NOV 83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 7 FEB 84 under the business name of Central Well & Pump Inc. by (signature) J. J. J. J.							
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.							