

1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County: Sedgwick		SE 1/4 SW 1/4 SW 1/4	15		T 29 S	R 1W E/W
Distance and direction from nearest town or city street address of well if located within city? 1/4 East of Ridge Rd, N side of 95th So. Wichita, Ks.						
2 WATER WELL OWNER: Bob Hay						
RR#, St. Address, Box # : 9171 S. West				Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Wichita, Ks. 67233				Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 48 ft. ELEVATION:				
1 Mile		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.				
		WELL'S STATIC WATER LEVEL 23 ft. below land surface measured on mo/day/yr 10-18-90				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
		Bore Hole Diameter. 11 in. to 48 ft., and in. to ft.				
WELL WATER TO BE USED AS:						
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)						
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well						
Was a chemical/bacteriological sample submitted to Department? Yes. No. X If yes, mo/day/yr sample was sub-						
mitted Water Well Disinfected? Yes X No						
5 TYPE OF BLANK CASING USED:						
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded						
2 PVC 4 ABS 7 Fiberglass SDR-26 Threaded						
Blank casing diameter 5 in. to 40 ft., Dia in. to ft., Dia in. to ft.						
Casing height above land surface. 12 in., weight 2.29 lbs./ft. Wall thickness or gauge No. .214						
TYPE OF SCREEN OR PERFORATION MATERIAL:						
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)						
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)						
SCREEN OR PERFORATION OPENINGS ARE:						
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)						
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes						
3 Torch cut 10 Other (specify)						
SCREEN-PERFORATED INTERVALS: From 40 ft. to 48 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
GRAVEL PACK INTERVALS: From 24 ft. to 48 ft., From ft. to ft.						
From ft. to ft., From ft. to ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other						
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft., From ft. to ft.						
What is the nearest source of possible contamination:						
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well						
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well						
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)						
13 Insecticide storage						
Direction from well? West How many feet? 85						
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS	
0	3	topsoil				
3	14	clay				
14	37	fine sand				
34	40	clay				
40	48	medium sand				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10-18-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 1-10-91 under the business name of Harp Well and Pump Service, Inc. by (signature) <i>Mary Arnold</i>						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4