


1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 SW 1/4 Section Number 9 Township Number 29 Range Number 1 E/W W
 County: Sedgwick
 Distance and direction from nearest town or city/street address of well if located within city? See Below

2 WATER WELL OWNER: Gary Helmers
 RR#, St. Address, Box #: 8010 W. 87th St. So.
 City, State, ZIP Code: Clearwater, KS 67026
 Board of Agriculture, Division of Water Resources
 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

 4 DEPTH OF COMPLETED WELL: 110 ft. ELEVATION: 8-9-94
 Depth(s) Groundwater Encountered 1. 30 ft. 2. 30 ft. 3. 30 ft.
 WELL'S STATIC WATER LEVEL 30 ft. below land surface measured on mo/day/yr 8-9-94
 Pump test data: Well water was 30 ft. after 1/2 hours pumping 20 gpm
 Est. Yield 40 gpm: Well water was 30 ft. after 1/2 hours pumping 20 gpm
 Bore Hole Diameter 11 in. to 110 ft. and 110 in. to 110 ft.
 WELL WATER TO BE USED AS:
☒ 1 Domestic ☐ 3 Feedlot ☐ 6 Oil field water supply ☐ 9 Dewatering ☐ 12 Other (Specify below)
☐ 2 Irrigation ☐ 4 Industrial ☐ 7 Lawn and garden only ☐ 10 Monitoring well
 Was a chemical/bacteriological sample submitted to Department? Yes X No X; If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes X No X

5 TYPE OF BLANK CASING USED:
☒ 1 Steel ☐ 3 RMP (SR) ☐ 5 Wrought iron ☐ 8 Concrete tile CASING JOINTS: Glued X Clamped X
☒ 2 PVC ☐ 4 ABS ☐ 6 Asbestos-Cement ☐ 9 Other (specify below) Welded X
 Blank casing diameter 5 in. to 1280 ft. Dia. 2.40 in. to 160 PSI lbs./ft. Wall thickness or gauge No. 160 PSI
 Casing height above land surface 1280 in., weight 2.40 lbs./ft.
 TYPE OF SCREEN OR PERFORATION MATERIAL:
☐ 1 Steel ☐ 3 Stainless steel ☐ 5 Fiberglass ☒ 7 PVC ☐ 10 Asbestos-cement
☐ 2 Brass ☐ 4 Galvanized steel ☐ 6 Concrete tile ☐ 8 RMP (SR) ☐ 11 Other (specify)
☐ 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE:
☐ 1 Continuous slot ☒ 3 Mill slot ☐ 5 Gauzed wrapped ☐ 8 Saw cut ☐ 11 None (open hole)
☐ 2 Louvered shutter ☐ 4 Key punched ☐ 6 Wire wrapped ☐ 9 Drilled holes
☐ 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 80 ft. to 110 ft. From 80 ft. to 110 ft.
 GRAVEL PACK INTERVALS: From 30 ft. to 110 ft. From 30 ft. to 110 ft.

6 GROUT MATERIAL: ☐ 1 Neat cement ☒ 2 Cement grout ☐ 3 Bentonite ☐ 4 Other
 Grout Intervals: From 3 ft. to 30 ft. From 30 ft. to 110 ft. From 110 ft. to 110 ft.
 What is the nearest source of possible contamination:
☐ 1 Septic tank ☐ 4 Lateral lines ☒ 7 Pit privy ☐ 10 Livestock pens ☐ 14 Abandoned water well
☐ 2 Sewer lines ☐ 5 Cess pool ☒ 8 Sewage lagoon ☐ 11 Fuel storage ☐ 15 Oil well/Gas well
☐ 3 Watertight sewer lines ☐ 6 Seepage pit ☐ 9 Feedyard ☐ 12 Fertilizer storage ☐ 16 Other (specify below)
☐ 13 Insecticide storage
 Direction from well? Northwest How many feet? 150

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Top Soil	68	70	gravel
2	62	clay	70	98	clay
62	64	gravel	98	110	Shale
64	68	clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-9-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 318 This Water Well Record was completed on (mo/day/yr) 8-12-94 under the business name of Weninger Drilling by (signature) Karina Morrissey