


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County KINGMAN	Fraction NW 1/4 SE 1/4 SW 1/4	Section number 10	Township number T. 29 S.	Range number R. 10W E/W
2. Distance and direction from nearest town or city: Street address of well location if in city:	1/2 N of St. Leo, Kas		3. Owner of well: Burne Albers R.R. or street: City, state, zip code: St. Leo, Kas		
4. Locate with "X" in section below: N W E S 1 Mile	Sketch map: 		6. Bore hole dia. 30 in. Completion date 15 NOV 77 Well depth 50 ft.		
5. Type and color of material	From	To	7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
Soil	0	2	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
SILT, Sandy	2	7	9. Casing: Material STL Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight <input type="checkbox"/> lbs./ft.		
Sand, fine to coarse & med gravel	7	15	Dia. 16 in. to 30 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 188		
Sand, fine to coarse w/ gray clay	15	23	10. Screen: Manufacturer's name Freeflo Type <input type="checkbox"/> Dia. 16 in. Slot/gauze 1/8 Length 30 ft. Set between 20 ft. and 50 ft. ft. and <input type="checkbox"/> ft.		
Sand, fine to coarse	23	34	Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/8 X 1/2		
Sand, fine to coarse & med gravel	34	37	11. Static water level: <input type="checkbox"/> mo./day/yr. 8 ft. below land surface Date 15 NOV 77		
Clay, brown w/ fine to coarse sand	37	39	12. Pumping level below land surfaces: 30 ft. after 1 1/2 hrs. pumping 150 g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 150 g.p.m.		
Sand, fine to med - loose	39	51	13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/> mo./day/yr.		
Clay, brown	51	54	14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade		
Sand, fine to med w/ red silt - dirty	54	65	15. Well grouted? <input checked="" type="checkbox"/> With: <input type="checkbox"/> Neat cement <input checked="" type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
Shale, Red	65	75	16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type None Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No		
			17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Goulds Model number 6TLC HP 10 Volts 440 Length of drop pipe 45 ft. capacity 100 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:	19. Remarks: 3'x3'x8" slot poured at Surface		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Central Well & Pump Svc. 325 Business name License No. Address 121 S. Taylor Pratt, Kas. Signed W. Monnick Date 24 July 78 Authorized representative		