


1 LOCATION OF WATER WELL: Kingman	FRACTION 1/4 1/4 1/4 NEAR C OF NW	Section Number 30	Township Number T 29 S	Range Number R 10W E/W
---	--	-----------------------------	----------------------------------	----------------------------------

Distance and direction from nearest town or city street address of well if located within city?

10 m. S., 1 3/4 m. W., 1/4 S. of Cunningham, Kansas

2 WATER WELL OWNER: SIMON FARMS RR#, ST. ADDRESS, BOX #: RR 2, Box 69 CITY, STATE, ZIP CODE: Cunningham, Kansas	Board of Agriculture, Division of Water Resource Application Number:
---	---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL 102 ft. ELEVATION: Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL 16.5 FT. BELOW LAND SURFACE MEASURED ON 04/13/1994 Pump test data: Well water was 46 ft. after 1 hours pumping 881 gpm Est. Yield gpm: Well water was 50 ft. after 1 hours pumping 950 gpm Bore Hole Diameter 30 in. to 102 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No
--	---

5 TYPE OF CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing Diameter 16 in. to 42 ft., Dia in. to ft., Dia in. to ft. Casing height above land surface 12 in., weight 42.05 lbs. / ft. Wall thickness or gauge No. .250 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole) SCREEN OR PERFORATION OPENING ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATION INTERVALS: from 42 ft. to 102 ft., From ft. to ft. GRAVEL PACK INTERVALS: from 20 ft. to 102 ft., From ft. to ft.	CASING JOINTS: Glued Clamped Welded X Threaded
---	---

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandon water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage None Apparent Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	INTERVALS
0	2	topsoil	96	102	tan clay with sand streaks
2	14	fine to coarse sand and fine gravel			
14	19	coarse sand and gravel			
19	25	very sandy tan clay			
25	30	fine to coarse sand and fine to medium gravel			
30	36	tan and white clay			
36	45	fine to coarse sand and fine to medium gravel			
45	66	fine to coarse sand and fine to coarse gravel loose			
66	74	brown clay w/ sand streaks			
74	96	fine to coarse sand and fine to medium gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/yr) 04/13/1994 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 04/30/94 Under the business name of Harp Well & Pump Service, Inc. by (signature)

Jane Frederick