

1 LOCATION OF WATER WELL: County: Pratt		Fraction SE 1/4 SE 1/4 SE 1/4	Section Number 30	Township Number T 29 S	Range Number R 11W E/W	
Distance and direction from nearest town or city street address of well if located within city? 6 E, 3/4 S of Sawyer, Kansas						
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :		William McGuire Red Tiger Drilling McGuire 1-30 Greensburg, Ks. 1720 Ks. State Bank Bldg. Board of Agriculture, Division of Water Resources 67054 Wichita, Ks. 67202 Application Number: T83-607				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 185 ft. ELEVATION: Unknown				
		Depth(s) Groundwater Encountered 1. 85 ft. 2. 85 ft. 3. 11/9/83 ft. WELL'S STATIC WATER LEVEL 85 ft. below land surface measured on mo/day/yr Pump test data: Well water was 60 gpm: Well water was 8 in. to 185 ft. after 11/9/83 hours pumping 11/9/83 gpm Bore Hole Diameter 8 in. to 185 ft. and 185 in. to 185 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 <u>Oil field water supply</u> 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted No Water Well Disinfected? Yes No				
		5 TYPE OF BLANK CASING USED:				
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: <u>Glued</u> <u>Clamped</u> 2 <u>PVC</u> 4 ABS 6 Asbestos-Cement 9 Other (specify below) <u>Welded</u> 7 Fiberglass <u>Threaded</u>				
		Blank casing diameter 5 in. to 165 ft. Dia 165 in. to 165 ft. Dia 165 in. to 165 ft. Casing height above land surface 12 in. weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40				
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 <u>PVC</u> 10 Asbestos-cement				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) 11		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole)				
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) 10				
SCREEN-PERFORATED INTERVALS: From 165 ft. to 185 ft. From 165 ft. to 185 ft. From 165 ft. to 185 ft.		GRAVEL PACK INTERVALS: From 10 ft. to 185 ft. From 10 ft. to 185 ft. From 10 ft. to 185 ft.				
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other		Grout Intervals: From 0 ft. to 10 ft. From 0 ft. to 10 ft. From 0 ft. to 10 ft.				
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well				
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 <u>Oil well/Gas well</u>		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)				
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? East How many feet? 60				
FROM	TO	LITHOLOGIC LOG		FROM	TO	LITHOLOGIC LOG
0	85	Clay				
85	95	Sand and Gravel				
95	165	Clay				
165	185	Sand and Gravel				
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/9/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 12/30/83 under the business name of Kellys Water Well Service by (signature) <i>Kellys Water Well Service</i>						
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

29

R

11

EDW

SEC. 30

SE 1/4 SE 1/4 SE 1/4

SE 1/4