


1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Pratt	NW 1/4 NW 1/4 NW 1/4	9	T 29 S	R 12 E/W

Distance and direction from nearest town or city street address of well if located within city?

2 3/4 N, 2 1/2 E, Sawyer, Ks.

2 WATER WELL OWNER:	Kent Brubaker	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # :	80499 Southwest 50th Ave.	Application Number: 43,191
City, State, ZIP Code :	Sawyer, Ks. 67134	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 205 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1 ft. 2. ft. 3. ft.
	WELL'S STATIC WATER LEVEL 71 ft. below land surface measured on mo/day/yr 3-31-99
	Pump test data: Well water was 85 1/2 ft. after 2 1/2 hours pumping 800 gpm
	Est. Yield 1200 gpm: Well water was 85 1/2 ft. after 2 1/2 hours pumping 800 gpm
	Bore Hole Diameter 28 in. to 205 ft., and in. to ft.
	WELL WATER TO BE USED AS:
	1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
	2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well
	Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted
	Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	10 Asbestos-cement
Blank casing diameter 16 in. to 145 ft., Dia			11 Other (specify)
Casing height above land surface 12 in., weight sch 40 lbs./ft. Wall thickness or gauge No.			12 None used (open hole)
TYPE OF SCREEN OR PERFORATION MATERIAL:			
1 Steel	3 Stainless steel	5 Fiberglass	7 PVC
2 Brass	4 Galvanized steel	6 Concrete tile	8 RMP (SR)
SCREEN OR PERFORATION OPENINGS ARE:			9 ABS
1 Continuous slot	3 Mill slot	5 Gauzed wrapped	8 Saw cut
2 Louvered shutter	4 Key punched	6 Wire wrapped	9 Drilled holes
7 Torch cut			11 None (open hole)
SCREEN-PERFORATED INTERVALS:			10 Other (specify)
From 145 ft. to 205 ft.			
GRAVEL PACK INTERVALS:			
From 205 ft. to 20 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other hole plug
Grout Intervals:	From 20 ft. to 0 ft.			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	house
Direction from well? South west			How many feet? 1/2 mile	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	Top soil	155	195	Sand and gravel medium to coarse
3	15	Brown clay	195	205	Sand and gravel fine to medium
15	16 1/2	Sandy brown clay			loose
16 1/2	20	Sand and gravel			
20	23	Yellow brown and gray clay			
23	35	Brown and white clay			
35	42	Sand and gravel			
42	50	Brown clay			
50	68	Sand and gravel with a little clay			
68	80	Brown clay			
80	84	Fine sand			
84	122	Sand and gravel medium loose			
122	128	Brown gray and white clay			
128	151	Sand and gravel loose			
151	155	Yellow brown gray and white clay			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-17-99 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 6-7-99 under the business name of Rosencrantz-Bemis by (signature) Fredia Hudson
--