WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

2. Distance and direction from nearest town or city: Street address of well location if in city: Cairo, KS Sketch map: 3. Owner of well: R.R. or street: City, state, zip code: City, state, zip code: A. Locate with "X" in section below: Sketch map: Sketch map: 6. Bore hole dia. 28 in. Completion date	County	Fraction	CN-	Ī	Section	number	Township number	Range number		
Street address of well location if in city: Cairo, KS R.R. or street: City, state, zip code: R.R. or street: City, state, zip code: Rotary	1. Location of well: Pratt	1/4				12	T 29	s R 12	L /W	
Street address of well location if in city: 4. Locate with "X" in section below: Sketch map: Sketch map: 6. Bore hole dia. 28 in. Completion date	2. Distance and direction from nearest town or city:	75 / 3	w			l:	Barker	B 405		
4. Locate with "X" in section below: Sketch map: Sketch map:	Street address of well location if in city:	ro, K	s			code: K	1 Fratt	KS		
7Cable toolRotaryDrivenDugHollow rodJettedBoredXReverse rotary 8. Use:DomesticPublic supplyIndustryXIrrigationAir conditioningStockLawnOil field waterOther 9. Casing: MaterialSTAHeight:Boover or below ThreadedWeldedWeldedSurface/2in. RMPPVCWeightIbs./ft. Diain. toOff. depth Wall Thickness: inches or Diain. toft. depth gage No3//Co. 10. Screen: Manufacturer's name		Sketch map:					6. Bore hole dia. 28;	n. Completion date	7	
Hollow rodJettedBored XReverse rotary 8. Use:DomesticPublic supplyIndustry										
S									e rotary	
Lawn Oil field water Other 9. Casing: Material A Height: Moore or below Threaded Welded X Surface 2 in. RMP PVC Weight Ibs./ft. Dia./bin. to 8 ft. depth Wall Thickness: inches or Dia. in. to ft. depth gage No. 3/16 10. Screen: Manufacturer's name	₩ E								' I	
Threaded	SW SE						Lawn	Oil field water Oth	er	
5. Type and color of material Dia. Lá in. to L8 ft. depth Wall Thickness: inches or Diain. toft. depth gage No3//6_ 10. Screen: Manufacturer's name										
5. Type and color of material From To Diain. toft. depth gage No3//6_ 10. Screen: Manufacturer's name	i									
1 DAGET					From	То			16_	
1	7.00%	C) (1	, Ai.		0	24	/1			
Top Soil - Sauld / Cldy 79 Type Steel Dia. 16" Slot/gauze 48" Length 60	10P2011-	Sandi	/ Cld	γ	-	19	Type Stee!	Dia	<u>—</u>	
5 de Nd /9 70 Set between 188 ft. and 168 ft.	3 de 10	(d			79	90	Set between	_ft. and	ft.	
Cldy 90 103 Gravel pack? X Size range of material 19-374	Cldy				90	103		11.0	3/4	
Sand - Frauel 103 124 11. Static water level: mo./day/yr. 80 ft. below land surface Date 2-11-77	Sand- E	ravel			103	124				
CEMENTED SANDS 124 130 12. Pumping level below land surfaces:	COMENY	ed 5a	Nds		124	130				
Sand- Grave/ 130/68 124 ft. after 4 hrs. pumping 1000g.p.m.	SANH	Ardue	1							
Estimated maximum yield	Jan	4,40	•				Estimated maximum yield	1300	g.p.m.	
13. Water sample submitted: mo./day/yr. Yes X No Date							· 🗚	,	аау/уг.	
14. Well head completion: Pitless adapter							'	12 Inches above ar	rade	
15. Well grouted?							15. Well grouted?			
With: X Neat cement Bentonite Concrete) Depth: From ft. to ft.									ncrete -	
16. Nearest source of possible contamination: None ft Direction Type							16. Nearest source of possib	le contamination: No	Ne	
Well disinfected upon completion? Yes No									3	
17. Pump: Manufacturer's name 40 ulss							· 4		1 1.	
Model number							Model number _5-125	HP /00 Volts		
Type:									3.p.m.	
									ating	
(Use a second sheet if needed) Centrifugal Other		neet if needed)						Other		
This well was drilled under my jurisdiction and this report	19. Kemarks:								eport	
Topography:	Topography:			".			is true to the best of my kno	wledge and belief. **//////////////////////////////////	1 = QX	
Business nome 2 Circuit Beings No. Address R 2 Circuit Beind NS								eat Bould	50 No.	
Wupland Valley Signed Kully Price Date 4-20-77 Authorized representative	Upland						Signed Killy	Price Date 5	2-2027	