

USE TYPEWRITER OR BALL
POINT PEN—PRESS FIRMLY,
PRINT CLEARLY.

Location?

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment—Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Pratt	Fraction C NE 1/4 NE 1/4 1/4 1/4	Section number 18	Township number T 29 S	Range number R 12 E																												
2. Distance and direction from nearest town or city: 2 mile North 1/2 mile East of Sawyer, Ks. Street address of well location if in city:			3. Owner of well: Joel Brubaker R.R. or street: Sawyer, Kansas 67134 City, state, zip code:																														
4. Locate with "X" in section below: N W E S 1 Mile 1 Mile		Sketch map: Well No. 5 (TH 1-76)		6. Bore hole dia. 30 in. Completion date 8/24/76 Well depth 204 ft.																													
<table border="1" style="width:100%; border-collapse: collapse;"> <tr> <td style="width:50%;">5. Type and color of material</td> <td style="width:10%;">From</td> <td style="width:10%;">To</td> </tr> <tr> <td>Top soil</td> <td>0</td> <td>2</td> </tr> <tr> <td>Clay with some sand</td> <td>2</td> <td>67</td> </tr> <tr> <td>Med. to coarse sand & gravel</td> <td>67</td> <td>151</td> </tr> <tr> <td>Sandy clay</td> <td>151</td> <td>158</td> </tr> <tr> <td>Med. to coarse sand & gravel w/clay</td> <td>158</td> <td>195</td> </tr> <tr> <td>Clay</td> <td>195</td> <td>198</td> </tr> <tr> <td>Med. to co. sand & gravel</td> <td>198</td> <td>204</td> </tr> <tr> <td>Red shale</td> <td>204</td> <td>209</td> </tr> <tr> <td colspan="3" style="text-align:center;">(Use a second sheet if needed)</td> </tr> </table>		5. Type and color of material	From	To	Top soil	0	2	Clay with some sand	2	67	Med. to coarse sand & gravel	67	151	Sandy clay	151	158	Med. to coarse sand & gravel w/clay	158	195	Clay	195	198	Med. to co. sand & gravel	198	204	Red shale	204	209	(Use a second sheet if needed)			7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary	
		5. Type and color of material	From	To																													
		Top soil	0	2																													
		Clay with some sand	2	67																													
Med. to coarse sand & gravel	67	151																															
Sandy clay	151	158																															
Med. to coarse sand & gravel w/clay	158	195																															
Clay	195	198																															
Med. to co. sand & gravel	198	204																															
Red shale	204	209																															
(Use a second sheet if needed)																																	
8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other																																	
9. Casing: Material Stl Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 31.75 lbs./ft. Dia. 16 in. to 137 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 188																																	
10. Screen: Manufacturer's name Doerr Metal Products Type Stl Dia. 16 " Slot/gauze 1/8 " Length 68 " Set between 126 ft. and 204 ft. ft. and <input type="checkbox"/> ft. Gravel pack Yes Size range of material 1/8 to 3/8																																	
11. Static water level: 83 ft. below land surface Date 7/24/76 mo./day/yr.																																	
12. Pumping level below land surfaces: 104 ft. after 2 1/2 hrs. pumping 800 g.p.m. <input type="checkbox"/> ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 1000 g.p.m.																																	
13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date <input type="checkbox"/> mo./day/yr.																																	
14. Well head completion: <input type="checkbox"/> Pitless adapter 12 Inches above grade																																	
15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.																																	
16. Nearest source of possible contamination: ft. 4500 Direction EAST Type FARM Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No																																	
17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Layne & Bowler Model number KL HP 30 Volts <input type="checkbox"/> Length of drop pipe 140 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other																																	
18. Elevation: 1901 Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley	19. Remarks: 27595 29 12 18 NAX																																
20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co. 102 Business name License No. Address Wichita, Kansas Signed [Signature] Date 8/13/76 Authorized representative																																	

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5