

USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:	County Pratt	Fraction C SW 1/4	Section number 27	Township number T 29 S	Range number R 12 E
2. Distance and direction from nearest town or city: 3 miles East & 1/2 South of Sawyer, Kansas		3. Owner of well: Bill Miller R.R. or street: Sawyer, Kansas 67134 City, state, zip code:			
4. Locate with "X" in section below: Well No. 1 (TH 1-76)		6. Bore hole dia. 30 in. Completion date 6/20/76 Well depth 196 ft.			
		7. Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
		8. Use: Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other <input type="checkbox"/>			
		9. Casing: Material Stl. Height: Above ground 12 in. Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 31.75 lbs./ft. Dia. 16 in. to 129 ft. depth Wall Thickness: inches or Dia. 16 in. to 129 ft. depth gage No. 188			
5. Type and color of material		From	To		
Top soil		0	2	10. Screen: Manufacturer's name Doerr Metal Products	
Clay		2	17	Type Stl. Dia. 16 " Slot/gauze 1/8 " Length 68 " Set between 129 ft. and 196 ft.	
Med. to coarse sand & med. gravel		17	56	Gravel pack? yes Size range of material 1/2 x 3/8	
Clay		56	76	11. Static water level: 82 ft. below land surface Date 6/24/76	
Med. to coarse sand & gravel w/some clay		76	196	12. Pumping level below land surfaces: 95 ft. after 2.5 hrs. pumping 900 g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 1000 g.p.m.	
Red shale		196	200	13. Water sample submitted: Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date	
				14. Well head completion: Pitless adapter 12 inches above grade	
				15. Well grouted? yes With: Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete <input type="checkbox"/> Depth: From 0 ft. to 10 ft.	
				16. Nearest source of possible contamination: ft. 2500 Direction SW Type Farm Well disinfected upon completion? Yes <input checked="" type="checkbox"/> No <input type="checkbox"/>	
				17. Pump: Not installed Manufacturer's name Layne & Bowler Model number 77185L HP 100 Volts Length of drop pipe 120 ft. capacity 800 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
18. Elevation: 1880		19. Remarks: 27721 29 12 27 NCX			
Topography: <input type="checkbox"/> Hill <input checked="" type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Layne Western Co. 102 Business name License No. Address Wichita, Kansas Signed [Signature] Date 6/28/76 Authorized representative			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5