

HIRT #1

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: <u>PRATT</u>	<u>SE 1/4 SE 1/4 NW 1/4</u>	<u>29</u>	T <u>29</u> S	R <u>12</u> E

Distance and direction from nearest town or city street address of well if located within city?

SAWYER 1/2E SOUTHSIDE2 WATER WELL OWNER: STERLING DRILLING CO.RR#, St. Address, Box #: BOX 129City, State, ZIP Code: STERLING KS 67579

Board of Agriculture, Division of Water Resources

Application Number: 783-640

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:

4 DEPTH OF COMPLETED WELL: 120 ft. ELEVATION:Depth(s) Groundwater Encountered 1. 95 ft. 2. 115.83 ft. 3. 115.83 ft.WELL'S STATIC WATER LEVEL 95 ft. below land surface measured on mo/day/yr 11-5-83Pump test data: Well water was 7.718 ft. after 120 hours pumping 11.5 gpmEst. Yield 11.5 gpm: Well water was 7.718 ft. after 120 hours pumping 11.5 gpmBore Hole Diameter 7.718 in. to 120 ft., and 120 in. to 120 ft.

WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well

1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)

2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well

Was a chemical/bacteriological sample submitted to Department? Yes NO No NO; If yes, mo/day/yr sample was submittedWater Well Disinfected? Yes NO No NO

5 TYPE OF BLANK CASING USED:

5 Wrought iron

8 Concrete tile

CASING JOINTS: Glued XY Clamped NO

1 Steel

3 RMP (SR)

6 Asbestos-Cement

9 Other (specify below)

Welded NO

2 PVC

4 ABS

7 Fiberglass

Threaded NOBlank casing diameter 5 in. to 100 ft., Dia 100 in. to 100 ft., Dia 100 in. to 100 ft.Casing height above land surface 12 in., weight 2.65 lbs./ft. Wall thickness or gauge No. 21.4

TYPE OF SCREEN OR PERFORATION MATERIAL:

1 Steel

3 Stainless steel

5 Fiberglass

7 PVC

10 Asbestos-cement

2 Brass

4 Galvanized steel

6 Concrete tile

8 RMP (SR)

11 Other (specify)

9 ABS

12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1/8

1 Continuous slot

3 Mill slot

5 Gauzed wrapped

8 Saw cut

11 None (open hole)

2 Louvered shutter

4 Key punched

6 Wire wrapped

9 Drilled holes

7 Torch cut

10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 100 ft. to 120 ft., From 100 ft. to 120 ft., From 100 ft. to 120 ft.GRAVEL PACK INTERVALS: From 95 ft. to 120 ft., From 95 ft. to 120 ft., From 95 ft. to 120 ft.

6 GROUT MATERIAL:

1 Neat cement

2 Cement grout

3 Bentonite

4 Other

Grout Intervals: From 0 ft. to 10 ft., From 0 ft. to 10 ft., From 0 ft. to 10 ft.What is the nearest source of possible contamination: NONE

1 Septic tank

4 Lateral lines

7 Pit privy

10 Livestock pens

14 Abandoned water well

2 Sewer lines

5 Cess pool

8 Sewage lagoon

11 Fuel storage

15 Oil well/Gas well

3 Watertight sewer lines

6 Seepage pit

9 Feedyard

12 Fertilizer storage

16 Other (specify below)

13 Insecticide storage

Direction from well?

How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	SOIL			
3	30	SANDY CLAY			
30	70	DRY SAND			
70	90	CLAY			
90	120	GRAVEL			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-5-83 and this record is true to the best of my knowledge and belief. KansasWater Well Contractor's License No. 789 This Water Well Record was completed on (mo/day/yr) 11-12-83under the business name of REISER WATER WELL SERVICE INC. by (signature) Rudolph ReiserINSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

B

OFFICE USE ONLY

T

R

E

SEC.

29

SE 1/4

SE 1/4

SE 1/4

1/4