

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Pratt	SE ¼ NE ¼ SE ¼	24	T 29 S	R 13 W EW

Distance and direction from nearest town or city street address of well if located within city?

½ N of Sawyer

2 WATER WELL OWNER: Dennis Mohler	Board of Agriculture, Division of Water Resources
RR#, St. Address, Box # : 90311 SE 30 th Ave	Application Number:
City, State, ZIP Code : Sawyer, Ks. 67134	

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 122 ft. ELEVATION:
	Depth(s) Groundwater Encountered: 1. 110 ft. 2. 14-19-02 ft. 3. 14-19-02 ft. WELL'S STATIC WATER LEVEL: 94 ft. below land surface measured on mo/day/yr Pump test data: Well water was 9 ft. after 122 hours pumping 20 gpm Est. Yield 20 gpm: Well water was 9 ft. after 122 hours pumping 20 gpm Bore Hole Diameter: 9 in. to 122 ft., and 9 in. to 122 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter: 1 ½ in. to 113 ft., Dia			Threaded
Casing height above land surface: 16 in., weight			lbs./ft. Wall thickness or gauge No. 250
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 113 ft. to 122 ft., From 113 ft. to 122 ft., From 113 ft. to 122 ft., From 113 ft. to 122 ft.			
GRAVEL PACK INTERVALS: From 23 ft. to 122 ft., From 23 ft. to 122 ft., From 23 ft. to 122 ft., From 23 ft. to 122 ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 113 ft. to 122 ft., From 113 ft. to 122 ft., From 113 ft. to 122 ft., From 113 ft. to 122 ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	14 Abandoned water well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	15 Oil well/Gas well
Direction from well? North			13 Insecticide storage	16 Other (specify below)
			How many feet? 200	

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	soil			
2	12	brown clay			
12	33	yellow clay			
33	35	fine sand			
35	72	sand			
72	82	white clay			
82	92	fine yellow sand & clay			
92	103	fine sand			
103	112	clean sand			
112	113	brown clay			
113	116	clay & sand			
116	122	sand			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11-19-02 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No. 140 This Water Well Record was completed on (mo/day/yr) 11-19-02 under the business name of Ly an xx Inc. by (signature) <i>[Signature]</i>
--