

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number	
County: Pratt	SE 1/4 SE 1/4 SE 1/4	4	T 29 S	R 13 E	
Distance and direction from nearest town or city street address of well if located within city? On The Corner of Hwy 28 & 70th Street. North Side of Rd					
2 WATER WELL OWNER: Crowder Consolidated					
RR#, St. Address, Box # : 151 SW 70th Street			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code : Sawyer, KS 67134			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL			
		120 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 84 ft. 2 ft. 3 ft.			
		WELL'S STATIC WATER LEVEL 84 ft. below land surface measured on mo/day/yr			
		Pump test data: Well water was ft. after hours pumping gpm			
Est. Yield gpm: Well water was ft. after hours pumping gpm		WELL WATER TO BE USED AS:			
X 1 Domestic		3 Feedlot	5 Public water supply	8 Air conditioning	
2 Irrigation		4 Industrial	6 Oil field water supply	11 Injection well	
		7 Domestic (lawn & garden)	9 Dewatering	12 Other (Specify below)	
		10 Monitoring well			
Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted					
Water Well Disinfected? Yes X No					
5 TYPE OF BLANK CASING USED:					
1 Steel		3 RMP (SR)	5 Wrought iron	8 Concrete tile	
X 2 PVC		4 ABS	6 Asbestos-Cement	9 Other (specify below)	
Blank casing diameter 5 1/4 in. to 12 in. Dia		7 Fiberglass	CASING JOINTS: Glued X Clamped		
Casing height above land surface 12 in., weight 160 lbs./ft. Wall thickness or gauge No.		Welded Threaded			
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel		3 Stainless Steel	5 Fiberglass	8 RMP (SR)	
2 Brass		4 Galvanized Steel	6 Concrete tile	9 ABS	
				10 Asbestos-Cement	
				11 Other (Specify)	
				12 None used (open hole)	
SCREEN OR PERFORATION OPENINGS ARE:					
X 1 Continuous slot		3 Mill slot	5 Gauzed wrapped	8 Saw cut	
2 Louvered shutter		4 Key punched	6 Wire wrapped	9 Drilled holes	
			7 Torch cut	10 Other (specify) ft.	
				11 None (open hole)	
SCREEN-PERFORATED INTERVALS: From 120 ft. to 100 ft., From ft. to ft.					
GRAVEL PACK INTERVALS: From 120 ft. to 42 ft., From 40 ft. to 21 ft.					
6 GROUT MATERIAL:					
1 Neat cement		2 Cement grout	3 Bentonite	4 Other	
Grout Intervals: From 42 ft. to 40 ft., From 21 ft. to 0 ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank		4 Lateral lines	7 Pit privy	10 Livestock pens	
2 Sewer lines		5 Cess pool	8 Sewage lagoon	11 Fuel storage	
3 Watertight sewer lines		6 Seepage pit	9 Feedyard	12 Fertilizer storage	
				13 Insecticide storage	
				14 Abandoned water well	
				15 Oil well/Gas well	
				16 Other (specify below)	
Direction from well? East How many feet? 120ft					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	5	Brown Top Soil			
5	15	Tan Clay			
15	25	Fine Sand			
25	50	Tan Clay			
50	55	Coarse Sand			
55	65	Tan Clay			
65	120	Fine Sand / Coarse Strands			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was X constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7-2-03 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 7-2-03 This Water Well Record was completed on (mo/day/yr) 7-2-03 under the business name of Crowder's Water Well by (signature) [Signature]					