

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number				
County: Pratt		NW 1/4 NW 1/4 SW 1/4	5	T 29 S	R 13 EW				
Distance and direction from nearest town or city street address of well if located within city? 5W 3 1/2 N OF SAWYER, KS									
2 WATER WELL OWNER: Slawson Drilling Company		Board of Agriculture, Division of Water Resources							
RR#, St. Address, Box #: Great Bend, Kansas		Lease: Meigs Application Number:							
City, State, ZIP Code:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION: 85 ft.							
N 1 Mile W E S <table border="1" style="margin: auto; text-align: center;"><tr><td>NW</td><td>NE</td></tr><tr><td>SW</td><td>SE</td></tr></table>		NW	NE	SW	SE	Depth(s) Groundwater Encountered 1. 85 ft. 2. 85 ft. 3. 85 ft.			
		NW	NE						
		SW	SE						
		WELL'S STATIC WATER LEVEL 85 ft. below land surface measured on mo/day/yr 10 Nov. 83							
		Pump test data: Well water was 100 gpm. Well water was 10 ft. after 140 hours pumping 10 gpm							
Est. Yield 100 gpm. Well water was 10 ft. after 140 hours pumping 10 gpm									
Bore Hole Diameter 10 in. to 140 ft., and 140 in. to 140 ft.									
5 TYPE OF BLANK CASING USED:		WELL WATER TO BE USED AS:							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		CASING JOINTS: Glued ☒ Clamped ☐							
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Welded ☐ Threaded ☐							
Blank casing diameter 5 in. to 120 ft. Dia 120 in. to 140 ft. Dia 140 in. to 140 ft.		Water Well Disinfected? Yes ☒ No ☐							
Casing height above land surface 12 in. weight 2.34 lbs./ft. Wall thickness or gauge No. 2.14									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
SCREEN OR PERFORATION OPENINGS ARE:		12 None used (open hole)							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft. From 120 ft. to 140 ft.									
GRAVEL PACK INTERVALS: From 10 ft. to 140 ft. From 10 ft. to 140 ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 140 ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
Direction from well?		How many feet? NONE							
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG				
0	2	Top soil							
2	26	Clay, tan							
26	41	Sand, fine to coarse and fine gravel							
41	80	Clay, brown							
80	110	Sand, coarse to very coarse gravel							
110	118	Clay, tan and caliche							
118	140	Sand, fine to coarse and fine to coarse gravel							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 10 Nov 83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 14 Feb 84 under the business name of Central Well & Pump Inc. by (signature) J. A. Anomich									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									

OFFICE USE ONLY

T

R

EW

SEC.

5

1/4

1/4

1/4

1/4

1/4

1/4

1/4