

1 LOCATION OF WATER WELL: County: Pratt		Fraction: 150S 1/4 SW 1/4 SW 1/4	Section Number: 32	Township Number: T 29 S	Range Number: R 13W E/W
Distance and direction from nearest town or city street address of well if located within city? 2 S, 4 3/4 W of Sawyer, Kansas					
2 WATER WELL OWNER: James Shriver RR#, St. Address, Box #: Coates, Ks. 67028 City, State, ZIP Code: Sterling, Kansas 67579		Sterling Drilling Co. Box 129 Sterling, Kansas 67579		Shriver A1-32 Board of Agriculture, Division of Water Resources Application Number: 910103	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 185 ft. ELEVATION: Unknown Depth(s) Groundwater Encountered: 1. 110 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL: 110 ft. below land surface measured on mo/day/yr 2/22/91 Pump test data: Well water was ft. after hours pumping gpm Est. Yield: 60 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter: 8 in. to 185 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 5 Public water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS Blank casing diameter: 5 in. to 165 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface: 12 in. weight 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 6 Asbestos-Cement 9 Other (specify below) Welded 7 Fiberglass Threaded TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 165 ft. to 185 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 20 ft. to 185 ft. From ft. to ft. From ft. to ft. From ft. to ft. From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft. From ft. to ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? South How many feet? 60					
FROM TO LITHOLOGIC LOG		FROM TO PLUGGING INTERVALS			
0	35	Clay			
35	95	Sand and gravel			
95	105	Clay			
105	185	Sand and gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2/22/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 3/31/91 under the business name of Kelly's Water Well Service by (signature) Kelly's Water Well Service					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					