

1 LOCATION OF WATER WELL: County: Pratt	Fraction NW ¼ NE ¼ NE ¼	Section Number 26	Township Number T 29 S	Range Number R 13 EW
---	-----------------------------------	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?

1½ miles west of Sawyer, Kansas

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	Gyp Hills Regional Solid Waste Management Authority P.O. Box 345 Pratt, KS 67124	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 85 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 68.5 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 68.5 ft. below land surface measured on mo/day/yr 4/5/95 Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 6 3/4 in. to 85 ft. and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 2 in. to 69 ft. Dia			Threaded X
Casing height above land surface 32 in. weight			lbs. ft. Wall thickness or gauge No. Schedule 40
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut 84	10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 69 ft. to ft. From ft. to ft.			
GRAVEL PACK INTERVALS: From 67 ft. to 85 ft. From ft. to ft.			

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Bentonite Chips 64-67
Grout Intervals: From 4 ft. to 64 ft. From ft. to ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? East				14 Abandoned water well
				15 Oil well Gas well
				16 Other (specify below)
				How many feet? 2000

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Silt, sandy organics			MW95-2
1	5	Sandy clay, red-brown			
5	13	Sand, fine-coarse			
13	16½	Silty Clay, yellow-brown			
16½	25	Sand, fine-coarse gravel			
25	33½	Silty Clay, brown with sandy clay			
33½	39	Sand, clayey, fine-coarse			
39	41	Sandy Clay, orange			
41	56	Sand, fine-coarse, gravel			
56	57½	Sandy Clay, yellow-brown			
57½	60	Silty Clay, yellow-brown			
60	62	Sand, clayey, fine-coarse			
62	65	Sandy clay, yellow-brown gravel			
65	69	Sand, fine-coarse, gravel			
69	85	Sand, fine-coarse, saturated			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4/2/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 527 This Water Well Record was completed on (mo/day/yr) 4/25/95 under the business name of GeoCore Services, Inc. by (signature) Dale Loh
--