

1 LOCATION OF WATER WELL: County: <b>Pratt</b>	Fraction <b>SE ¼ NW ¼ SE ¼</b>	Section Number <b>26</b>	Township Number <b>T 29 S</b>	Range Number <b>R 13 EW</b>
---	-----------------------------------	-----------------------------	----------------------------------	--------------------------------

Distance and direction from nearest town or city street address of well if located within city?  
**1½ miles west and ¼ mile south of Sawyer, KS**

2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code :	<b>Gyp Hills Regional Solid Waste Management Authority</b> <b>P.O. Box 345</b> <b>Pratt, KS 67124</b>	Board of Agriculture, Division of Water Resources Application Number:
---	---	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: <b>100</b> ft. ELEVATION:
	Depth(s) Groundwater Encountered <b>1. 83.5</b> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <b>83.6</b> ft. below land surface measured on mo/day/yr <b>4/3/95</b> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <b>6. 3/4</b> in. to <b>100</b> ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only <b>10</b> Monitoring well 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No <b>X</b> ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No <b>X</b>

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
<b>2</b> PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter <b>2</b> in. to <b>84</b> ft. Dia			Threaded <b>X</b>
Casing height above land surface <b>26</b> in., weight			lbs. ft. Wall thickness or gauge No. <b>Schedule 40</b>
TYPE OF SCREEN OR PERFORATION MATERIAL:	<b>7</b> PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	<b>3</b> Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From <b>84</b> ft. to	ft. From	ft. to
GRAVEL PACK INTERVALS:	From <b>81</b> ft. to <b>100</b> ft.	ft. From	ft. to

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	<b>3</b> Bentonite	4 Other <b>Bentonite Chips 77-81</b>
Grout intervals: From <b>4</b> ft. to <b>77</b> ft.				
What is the nearest source of possible contamination:	1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens
	2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage
	3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage
				13 Insecticide storage
Direction from well? <b>West</b>				How many feet? <b>300</b>

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	1	Silt, sandy, caliche			MW95-3
1	9	Silty Clay, red-brown, caliche			
9	14½	Sandy Clay, orange, caliche			
14½	15½	Sandstone, broken, caliche			
15½	28	Sand, silty, fine-coarse			
28	30	Sand, fine-coarse, oily gravel			
30	33	Sand, clayey, fine-coarse			
33	37	Silty Clay, yellow-brown			
37	40	Sandy Clay, yellow-brown			
40	47½	Silty Clay, orange with sandy clay			
47½	55	Sand, fine-coarse, moist			
55	65	Sand, fine-coarse with gravel cobbles			
65	69	Sand, clayey, fine-coarse			
69	84	Sand, fine-coarse, gravel			
84	100	Sand, fine-coarse, saturated			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was <b>(1)</b> constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>3/30/95</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. This Water Well Record was completed on (mo/day/yr) <b>4/25/95</b> under the business name of <b>GeoCore Services, Inc.</b> by (signature) <i>Deke Rohl</i>
---