


1 LOCATION OF WATER WELL: County Pratt		Fraction C $\frac{1}{4}$ SE $\frac{1}{4}$ NW $\frac{1}{4}$	Section Number 36	Township Number T 29 S	Range Number R 14W E/W
Distance and direction from nearest town or city street address of well if located within city? 1/2 E, 2 1/2 S of Coates, Kansas					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		Joan Benson Red Tiger Sawyer, Ks. 1720 Ks. State Bank Bldg. 67134 Wichita, Ks. 67202		Benson 1-36 Board of Agriculture, Division of Water Resources Application Number: T83-624	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 172 ft. ELEVATION: Unknown Depth(s) Groundwater Encountered 1. 72 ft. 2. 72 ft. 3. 11 12/17/83 ft. WELL'S STATIC WATER LEVEL 72 ft. below land surface measured on mo/day/yr Pump test data: Well water was 60 gpm: Well water was 8 in. to 172 ft. and 11 12/17/83 ft. Est. Yield 60 gpm: Well water was 8 in. to 172 ft. and 11 12/17/83 ft. Bore Hole Diameter 8 in. to 172 ft. and 11 12/17/83 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 <u>Oil field water supply</u> 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) <u>2 PVC</u> 4 ABS		5 Wrought iron 8 Concrete tile 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass		CASING JOINTS: <u>Glued</u> Clamped Welded Threaded	
Blank casing diameter 5 in. to 152 ft. Dia. 12 in. to 2.8 lbs./ft. Wall thickness or gauge No. Sch. 40					
Casing height above land surface 12 in. weight 2.8 lbs./ft.					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 <u>Saw cut</u> 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 152 ft. to 172 ft. From 10 ft. to 172 ft.					
GRAVEL PACK INTERVALS: From 10 ft. to 172 ft. From 10 ft. to 172 ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 <u>Bentonite</u> 4 Other					
Grout Intervals: From 0 ft. to 10 ft. From 10 ft. to 172 ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) Direction from well? South How many feet? 60					
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	15	Clay			
15	172	Sand and Gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/17/83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 186 This Water Well Record was completed on (mo/day/yr) 12/30/83 under the business name of Kellys Water Well Service by (signature) <i>Deey Sord</i>					
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.					