

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Pratt		SE 1/4 SE 1/4 NW 1/4	11	T 29 S	R 14 EW
Distance and direction from nearest town or city street address of well if located within city? 1 1/2 N 3/8 E OF COATS, KS					

2 WATER WELL OWNER: F W A Drilling		Board of Agriculture, Division of Water Resources
RR#, St. Address, Box #: Box 970		
City, State, ZIP Code: Yukon, Oklahoma 73099		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		Lease: Norris #1 Application Number:

	4 DEPTH OF COMPLETED WELL: 140 ft. ELEVATION: 105 ft.	
	Depth(s) Groundwater Encountered 1. 105 ft. 2. 105 ft. 3. 105 ft.	
	WELL'S STATIC WATER LEVEL 105 ft. below land surface measured on mo/day/yr 12 Nov. 83	
	Pump test data: Well water was 100 gpm. Well water was 100 gpm.	
	Bore Hole Diameter 10 in. to 140 ft., and 140 in. to 140 ft.	
WELL WATER TO BE USED AS:		
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well		
Was a chemical/bacteriological sample submitted to Department? Yes X No X If yes, mo/day/yr sample was submitted 12 Nov. 83		
Water Well Disinfected? Yes X No X		

5 TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped X
1 Steel		6 Asbestos-Cement	9 Other (specify below)	Welded X
2 PVC		7 Fiberglass		Threaded X
3 RMP (SR)				
4 ABS				
Blank casing diameter 5 in. to 120 ft., Dia 120 in. to 120 ft., Dia 120 in. to 120 ft.				
Casing height above land surface 12 in., weight 2.34 lbs./ft. Wall thickness or gauge No. 2/4				
TYPE OF SCREEN OR PERFORATION MATERIAL:				
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement				
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)				
12 None used (open hole)				
SCREEN OR PERFORATION OPENINGS ARE:				
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)				
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes				
7 Torch cut 10 Other (specify)				
SCREEN-PERFORATED INTERVALS: From 120 ft. to 140 ft., From 120 ft. to 140 ft.				
GRAVEL PACK INTERVALS: From 10 ft. to 140 ft., From 10 ft. to 140 ft.				

6 GROUT MATERIAL:		1 Neat cement	2 Cement grout	3 Bentonite	4 Other
Grout Intervals: From 0 ft. to 10 ft., From 10 ft. to 140 ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) NONE					
Direction from well? 14 FEB 84					

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	2	Top soil			
2	47	0/ Clay, tan and white			
47	77	1/ Sand, fine to coarse and fine to coarse gravel			
77	90	0/ Clay, brown			
90	140	1/ Sand, fine to coarse and fine to very coarse gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12 Nov. 83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 14 FEB 84 under the business name of Central Well & Pump Inc. by (signature) [Signature]	
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.	

OFFICE USE ONLY

T

R

EED

SEC.

SE 1/4 SE 1/4 NW 1/4