

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
Pratt		SW 1/4 SW 1/4 SWNW 1/4		NW 4		T 29 S		R 15 E	
Distance and direction from nearest town or city street address of well if located within city?									
5 south, 4 west, 3/8 south, 630' east of Cullison, Kansas									
2 WATER WELL OWNER: Robert-Gay, Energy Enterprises									
RR#, St. Address, Box # : 1006 N. Main									
City, State, ZIP Code : Hutchinson, Kansas 67501 Lease: Bolser # 4									
Board of Agriculture, Division of Water Resources									
Application Number:									
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:									
4 DEPTH OF COMPLETED WELL: 80 ft. ELEVATION:									
Depth(s) Groundwater Encountered 1. 27 ft. 2. ft. 3. ft.									
WELL'S STATIC WATER LEVEL 27 ft. below land surface measured on mo/day/yr 9 Oct. 84									
Pump test data: Well water was ft. after hours pumping gpm									
Est. Yield 100 gpm: Well water was ft. after hours pumping gpm									
Bore Hole Diameter 10 in. to 80 ft. and in. to ft.									
WELL WATER TO BE USED AS:									
1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well									
2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below)									
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted									
Water Well Disinfected? Yes X No									
5 TYPE OF BLANK CASING USED:									
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped									
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded									
7 Fiberglass Threaded									
Blank casing diameter 5 in. to 60 ft. Dia. in. to ft. Dia. in. to ft.									
Casing height above land surface 12 in., weight 2.34 lbs./ft. Wall thickness or gauge No. 214									
TYPE OF SCREEN OR PERFORATION MATERIAL:									
1 Steel 3 Stainless steel 5 Fiberglass 7 RMP (SR) 10 Asbestos-cement									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)									
12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes									
7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 60 ft. to 80 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 10 ft. to 80 ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout intervals: From 0 ft. to 10 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
13 Insecticide storage None									
Direction from well? How many feet?									
FROM TO LITHOLOGIC LOG FROM TO LITHOLOGIC LOG									
0 2 04 Soil, sandy									
2 18 05 Sand, fine to coarse									
18 22 01 Clay, blue									
22 56 Sand, coarse and coarse gravel									
56 80 17 Sand, coarse and coarse gravel with boulders									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 29 Oct. 84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 325 This Water Well Record was completed on (mo/day/yr) 30 Jan. 85 under the business name of Central well & Pump Inc. by (signature) J. Honan									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									