


USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD  
KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:		County <b>Pratt</b>	Fraction 1/4 1/4 CSW 1/4	Section number <b>17</b>	Township number T 29 S R 15	Range number <b>EW</b>
2. Distance and direction from nearest town or city: <b>9 mi. West of Coats, KS</b> Street address of well location if in city:				3. Owner of well: <del>XXXXXXXXXX</del> <b>Pat Howell</b> R.R. or street: <b>601 S. Mound</b> City, state, zip code: <b>Pratt, KS 67124</b>		
4. Locate with "X" in section below: N W E S 1 Mile				Sketch map: 		
5. Type and color of material				From	To	
Top soil				0	3	
Brown clay				3	10	
Sand & gravel				10	42	
Brown clay				42	45	
Sand & gravel				45	87	
Brown clay & limestone				87	96	
Sand & gravel				96	126	
Hard sandstone				126	127	
(Use a second sheet if needed)						
18. Elevation: <b>2030</b>		19. Remarks: <b>24 719</b>  <b>24 15 17 NC Y</b>				
Topography: ___ Hill ___ Slope ___ Upland ___ Valley		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. <b>185</b> <b>Clarke Well &amp; Equipment, Inc.</b> Business name License No. Address <b>Great Bend, KS</b> Signed <b>D. W. Clarke</b> Date <b>12-6-75</b> Authorized representative				

6. Bore hole dia. 24 in. Completion date 12-5-75  
Well depth 127 ft.

7. \_\_\_ Cable tool \_\_\_ Rotary \_\_\_ Driven \_\_\_ Dug  
\_\_\_ Hollow rod \_\_\_ Jetted \_\_\_ Bored  Reverse rotary

8. Use: \_\_\_ Domestic \_\_\_ Public supply \_\_\_ Industry  
 Irrigation \_\_\_ Air conditioning \_\_\_ Stock  
\_\_\_ Lawn \_\_\_ Oil field water \_\_\_ Other

9. Casing: Material Steel Height: Above or below  
Threaded \_\_\_ Welded  Surface 12 in.  
RMP \_\_\_ PVC \_\_\_ Weight 30.3 lbs./ft.  
Dia. 16 in. to 97 ft. depth Wall Thickness: inches or  
Dia. \_\_\_ in. to \_\_\_ ft. depth gage No. 7 ga.

10. Screen: Manufacturer's name Doerr (D.) & Johnson Screen (J.D.) 125  
Type Double-slot & Dia. 16"  
Slot gauze 1/8 Length 30'  
Set between (D.) 97 ft. and 117 ft.  
(J.D.) 117 ft. and 127 ft.  
Gravel pack? Yes Size range of material 3/8-200

11. Static water level: \_\_\_ mo./day/yr.  
69 ft. below land surface Date 11-21-75

12. Pumping level below land surfaces: N/C  
\_\_\_ ft. after \_\_\_ hrs. pumping \_\_\_ g.p.m.  
\_\_\_ ft. after \_\_\_ hrs. pumping \_\_\_ g.p.m.  
Estimated maximum yield \_\_\_ g.p.m.

13. Water sample submitted: \_\_\_ mo./day/yr.  
Yes  No \_\_\_ Date \_\_\_

14. Well head completion:  
\_\_\_ Pitless adapter 12 Inches above grade

15. Well grouted? Yes  
With:  Neat cement \_\_\_ Bentonite \_\_\_ Concrete  
Depth: From 0 ft. to 10 ft.

16. Nearest source of possible contamination:  
ft. \_\_\_ Direction \_\_\_ Type \_\_\_  
Well disinfected upon completion? \_\_\_ Yes  No \_\_\_

17. Pump:  Not installed  
Manufacturer's name FMC Corp. / Peerless  
Model number 12LB-3 HP 80 Volts \_\_\_  
Length of drop pipe none ft. capacity 900 g.p.m.  
Type:  
\_\_\_ Submersible \_\_\_ Turbine   
\_\_\_ Jet \_\_\_ Reciprocating  
\_\_\_ Centrifugal \_\_\_ Other

Irr. 29 150 17 1/4 1/4 CSW

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5