


1 LOCATION OF WATER WELL: County: Pratt	Fraction NW SE $\frac{1}{4}$ SE $\frac{1}{4}$	Section Number 36	Township Number T 29 S	Range Number R 15 E/NE
---	--	--------------------------	--------------------------------------	--------------------------------------

Distance and direction from nearest town or city street address of well if located within city?

4 w 2 1/2 S Coats

2 WATER WELL OWNER: John Cromer RR#, St. Address, Box # : R 1 City, State, ZIP Code : Pratt, Kansas 67124	Board of Agriculture, Division of Water Resources Application Number:
--	--

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 	4 DEPTH OF COMPLETED WELL: 61 ft. ELEVATION: Depth(s) Groundwater Encountered 1. 20 ft. 2. 17 ft. 3. 4-21-90 ft. WELL'S STATIC WATER LEVEL 17 ft. below land surface measured on mo/day/yr Pump test data: Well water was 10 gpm: Well water was 61 ft. after 10 hours pumping 10 gpm Est. Yield 10 gpm: Well water was 61 ft. after 10 hours pumping 10 gpm Bore Hole Diameter 9 in. to 61 ft., and 61 in. to 61 ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No
--	--

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 5 in. to 55 ft., Dia. 55 in. to 55 ft., Dia. 55 in. to 55 ft. Casing height above land surface 18 in., weight 18 lbs./ft. Wall thickness or gauge No. 215 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 8 RMP (SR) 11 Other (specify) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 55 ft. to 59 ft., From 59 ft. to 59 ft., From 59 ft. to 59 ft. GRAVEL PACK INTERVALS: From 20 ft. to 61 ft., From 61 ft. to 61 ft., From 61 ft. to 61 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 20 ft., From 20 ft. to 20 ft., From 20 ft. to 20 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? N How many feet? 175

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	soil			
4	13	clay			
13	14	sand			
14	16	coarse dirty sand			
16	41	clay			
41	45	fine dirty sand			
45	52	clay			
52	60	med sand with clay mix			
60	61	shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-21-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 140 This Water Well Record was completed on (mo/day/yr) 5-4-90 under the business name of LYMAN Inc. by (signature) Alan Lyman
