at a		form WWC			sion of Water		W.11 ID
Original Record		Change in We			urces App. No		Well ID
1 LOCATION OF W County: Kiow		Fracti	on SW 1/4 NE 1/	NW Sect	tion Number Z 3	Township Numb	Range Number R 17 🗆 E K W
2 WELL OWNER: La		First:					(if unknown, distance and
Business: Magella	n Ammonia	· Pipelilan	,				
Address: One Wi	lliams Cpu	ater	_	From M	54. 4 76	+5 Ave., 5W of	r's address, check here: Haviland 90
Address: MD/2	7	AV		•			,
City: Tulsa	T	te: 6K ZIP:				76th Ave. 4	
3 LOCATE WELL	4 DEPTH O	F COMPLET	ED WELL:	475 ft	5 Latitud	le: 37,5099	(decimal degrees)
WITH "X" IN	Depth(s) Groun	ndwater Encount	ered: 1)	4.1. ft.	Longit	nde - 99, 15/3	(decimal degrees)
SECTION BOX:	2)	ft. 3)	ft., or 4)	Dry Well		□ WGS 84 □ X' NAI	
WELL'S STATIC WATER LEVEL:						for Latitude/Longitude	
below land surface, measured on (mo-day-			y-yr)		(unit make/model:)		
			-yr)	(WAAS enabled? \(\subseteq \text{ Yes} \subseteq \text{No} \)			
	Pump test data: Well water was ft.				☐ Lar	nd Survey Topogr	aphic Map
W					∑ YOn	. وهجي: line Mapper	le Barth
SW SE	Well water was ft.					v	
	arter Hours pumping				6 Elevati	on: 1975 ft	. K Ground Level 🔲 TOC
S	Para Hala Diar	a:gpm	in to 47	5 ft and	Source: Land Survey GPS Topographic Map		
1 mile				II. and	Other Google Earth		
7 WELL WATER TO	RETISED AS:		III. W	1t.			
1. Domestic:		• ublic Water Sup _j	nlv: well ID		10 🗀 Oil	Field Water Supply: 1	ease
Household		ewatering: how				ole: well ID	
Lawn & Garden	7. \Box A	auifer Recharge	: well ID			ed Uncased U	
Livestock	8. 🗷 M	quifer Recharge Ionitoring: well	$_{ m ID}$ \mathcal{M} \mathcal{W}	-4		rmal: how many bore	
2. Irrigation						sed Loop 🔲 Horizon	
3. ☐ Feedlot	☐ Ai	ir Sparge	☐ Soil Vapor	Extraction	b) Ope	en Loop 🔲 Surface Di	ischarge 🔲 Inj. of Water
4. ☐ Industrial	□ Re	ecovery	☐ Injection		13. 🗌 Oth	er (specify):	
Was a chemical/bacter	iological sampl	le submitted t	o KDHE?	Yes 🗷 No	If yes, date	sample was submitte	ed:
Water well disinfected?	☐ Yes 🗡 No)					
8 TYPE OF CASING	USED: ☐ Stee	I X PVC □ O	ther	CASIN	IG JOINTS:	☐ Glued ☐ Clampe	d Welded Threaded
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft.							
Casing diameter	in. toب. جي ا		ter	. in. to	п., Diame	ter in. to	II.
Casing height above land	surface3.	<i>Q</i> in. W	eight	. in. to lbs./ft.	ft., Diame Wall thickn	ter	24.40 T
Casing diameter	surface3.	<i>Q</i> in. W	eight	in. to	Wall thickn	ess or gauge No	24.40.
Casing height above land a TYPE OF SCREEN OF Steel Stain	surface3.6 R PERFORATIOnless Steel	<i>Q</i> in. W	eight	? 1bs./ft.	Wall thickn ☐ Othe	ess or gauge No	2h.40"
Casing height above land a TYPE OF SCREEN OF Steel Stain Brass Galv	surface	Q in. W ON MATERIA □ Fiberglass □ Concrete tile	eight	in. to	Wall thickn ☐ Othe	ess or gauge No	24.40.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR	surface	<i>Q</i> in. WDN MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE:	eight	lbs./ft.	Wall thickn ☐ Othe	ress or gauge No	2h.40
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	Q in. W DN MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W	eight	lbs./ft. used (open hole orch Cut	Wall thickn ☐ Othe c) rilled Holes	ress or gauge No	24.40.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	 C in. W DN MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W ☐ Wire Wr 	eight	lbs./ft. used (open hole orch Cut □ D aw Cut □ N	Wall thickn ☐ Othe Trilled Holes Tone (Open Ho	r (Specify)	2h.40
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot	surface	 C in. W DN MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W ☐ Wire Wr 	eight	lbs./ft. used (open hole orch Cut □ D aw Cut □ N	Wall thickn ☐ Othe Trilled Holes Tone (Open Ho	r (Specify)	2h.40
Casing height above land a TYPE OF SCREEN OF Steel Stain Brass Galve SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATION GRAVEL PAGE	surface	O in. W ON MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W I ☐ Wire Wra S: From 3.2 S: From 3.2	eight	used (open hole orch Cut D aw Cut N ft., From	Wall thickn Other Tilled Holes Ione (Open Ho The to The to	cr (Specify)	2.L. 48
Casing height above land a TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAGE 9 GROUT MATERIA	surface	C in. W ON MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W I ☐ Wire Wra S: From .3.2 Ment ☐ Cemer	eight	used (open hole orch Cut D aw Cut N ft., From entonite D	Wall thickn	cr (Specify)	ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From	Surface	O in. W ON MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W I ☐ Wire Wra S: From .3. CS: From .3. ment ☐ Cemen .3. ft., Fr	eight	used (open hole orch Cut D aw Cut N ft., From entonite D	Wall thickn	cr (Specify)	ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possible	Surface	O in. W ON MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W I ☐ Wire Wr: S: From 30 nent ☐ Cemer 30 ft., Fr	eight	used (open hole orch Cut D aw Cut N ft., From ft., From entonite C ft. to	Wall thickn Other Other Other One (Open Ho ft. to other other ft., From	cr (Specify)	2.L. 48
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATE GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possible Septic Tank	Surface	O in. W ON MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W I ☐ Wire Wrz S: From .3. check ☐ Cemen .3. in. ft., Fr eral Lines	eight	used (open hole orch Cut D aw Cut N ft., From entonite C ft. to	Wall thickn Other Other Other One (Open Ho ft. to ther ft., From Livestock Pen	Other (Specify)	ft. to ft ft ft. of ft f
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines	Surface	O in. W ON MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W I ☐ Wire Wra S: From .3. CS: From .3. inent ☐ Cemer inent ☐ Ce	eight	used (open hole orch Cut D aw Cut N ft., From ft., From entonite C ft. to	Wall thickn Other Tilled Holes Ione (Open Ho ther ft. to ther Livestock Pen Fuel Storage	Other (Specify)	2.L. 48
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line	Surface	O in. W ON MATERIA ☐ Fiberglass ☐ Concrete tile NGS ARE: ☐ Gauze W I ☐ Wire Wre S: From S. S: From From S. eral Lines ss Pool page Pit	eight	used (open hole orch Cut D aw Cut N ft., From entonite C agoon D agoon	Wall thickn Other Tilled Holes Ione (Open Ho The to The ft. to The ft., From Livestock Pen Fuel Storage Fertilizer Stor	Other (Specify)	ft. to ft ft ft. of ft ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line	Surface	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W Wire Wr S: From 30 nent Cemer Cemer The Frest Concrete tile Fiberglass Frest Concrete tile Fiberglass Gauze W Frest Concrete tile Fiberglass Gauze W Frest Concrete tile Fiberglass Gauze W Frest Concrete tile Fiberglass Frest Concrete tile Frest Concrete ti	eight	used (open hole orch Cut \Box aw Cut \Box No. ft., From entonite \Box oft. to	Wall thickn Other Other Orilled Holes I to the	Other (Specify)	ft. to ft. to ft. ft. ft. ft. to ft. ft. to ft. ft. ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT! GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Mother (Specify) Direction from well? 10 FROM TO	surface	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W Wire Wre S: From 30 nent Cement thing free free free free free free free fre	eight	used (open hole orch Cut \Box aw Cut \Box No. ft., From entonite \Box oft. to	Wall thickn Other Other Orilled Holes I to the	Other (Specify)	ft. to ft ft ft. of ft
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT! GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Watertight Sewer Line Cotor of Possible Direction from well?	Surface	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W Wire Wre S: From 30 nent Cemen certal Lines ss Pool page Pit CHOLOGIC LO	eight	used (open hole orch Cut D aw Cut N ft., From . entonite C ft. to	Wall thickn Other Other Orilled Holes Ione (Open Holes In to the to the	Other (Specify)	ft. to ft. to ft. ft. ft. ft. to ft. ft. to ft. ft. ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT! GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Mother (Specify) Direction from well? 10 FROM TO	Surface	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W Wire Wre S: From 30 nent Cemen certal Lines ss Pool page Pit CHOLOGIC LO	eight	used (open hole orch Cut D aw Cut N ft., From . entonite C ft. to	Wall thickn Other Other Orilled Holes Ione (Open Holes In to the to the	Other (Specify)	ft. to ft. to ft. ft. ft. ft. to ft. ft. to ft. ft. ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT! GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Watertight Sewer Line Cotor of Possible Direction from well?	R PERFORATION OPENITATION OPEN	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W. Wire Wre S: From 32. S: From 4. Cemeral Lines Seral Lines	eight	used (open hole orch Cut D aw Cut N ft., From . entonite C ft. to	Wall thickn Other Other Orilled Holes Ione (Open Holes In to the to the	Other (Specify)	ft. to ft. to ft. ft. ft. ft. to ft. ft. to ft. ft. ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lines Watertight Sewer Lines Other (Specify) Direction from well? 10 FROM TO O (O) O (S) 15	R PERFORATION PERFORATION OPENION MILE STATE STA	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W. Wire Wre S: From 32. S: From 4. Cemeral Lines Seral Lines	eight	used (open hole orch Cut D aw Cut N T. ft., From . ft., From . entonite C ft. to	Wall thickn Other Other Orilled Holes Ione (Open Holes In to the to the	Other (Specify)	ft. to ft. to ft. ft. ft. ft. to ft. ft. to ft. ft. ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lines Watertight Sewer Lines Other (Specify) Direction from well? 10 FROM TO O (O) O (S)	R PERFORATION PERFORATION OPENION MILE STATE STA	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W. Wire Wre S: From 3.2. S: From 4.2. Cement Cem	eight	used (open hole orch Cut D aw Cut N T. ft., From . ft., From . entonite C ft. to	Wall thickn Other Other Orilled Holes Ione (Open Holes In to the to the	Other (Specify)	ft. to ft. to ft. ft. ft. ft. to ft. ft. to ft. ft. ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lines Watertight Sewer Lines Other (Specify) Direction from well? 10 FROM TO O (O) O (S) 15	R PERFORATION PERFORATION OPENION MILE STATE STA	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W. Wire Wre S: From 3.2. S: From 4.2. Cement Cem	eight	used (open hole orch Cut D aw Cut N T. ft., From . ft., From . entonite C ft. to	Wall thickn Other Other Orilled Holes Ione (Open Holes In to the to the	Other (Specify)	ft. to ft. to ft. ft. ft. ft. to ft. ft. to ft. ft. ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lines Watertight Sewer Lines Other (Specify) Direction from well? 10 FROM TO O (O) O (S) 15	R PERFORATION PERFORATION OPENION MILE STATE STA	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W. Wire Wre S: From 3.2. S: From 4.2. Cement Cem	eight	used (open hole orch Cut D aw Cut N T. ft., From . ft., From . entonite C ft. to	Wall thickn Other Other Orilled Holes Ione (Open Holes In to the to the	Other (Specify)	ft. to ft. to ft. ft. ft. ft. to ft. ft. to ft. ft. ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAC 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lines Watertight Sewer Lines Other (Specify) Direction from well? 10 FROM TO O (O) O (S) 15	R PERFORATION PERFORATION OPENION MILE STATE STA	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W. Wire Wre S: From 3.2. S: From 4.2. Cemeral Lines Ses Pool Spage Pit Chologic Lo	eight	used (open hole orch Cut	Wall thickn Other Other Orilled Holes Ione (Open Holes In to the to the	Other (Specify)	ft. to ft. to ft. ft. ft. ft. to ft. ft. to ft. ft. ft. to ft.
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT! GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO O (O) O (S)	R PERFORATION OPENITATION OPEN	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W Wire Wr. S: From 3.2 nent Cemeration of the page Pit Line CHOLOGIC LOCAL Sand	eight	used (open hole orch Cut	Wall thickn Other Other Orilled Holes Ione (Open Ho In to Other It to Other Livestock Pen Fuel Storage Fertilizer Stor TO	cr (Specify)	ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Lines Watertight Sewer Lines Other (Specify) Direction from well? 10 FROM TO O (O) O (S) L5 40 40 47, 5	SOR LANDOV	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W Wire Wra S: From .3.2 S: From .3.6 Anent Cemen Cemen	eight	used (open hole orch Cut D aw Cut N St., From . St., From . entonite C agoon D well? SROM	Wall thickn Other Trilled Holes Ione (Open Ho The ft. to Other The ft., From Livestock Pen Fuel Storage Fertilizer Stor TO	cr (Specify)	ft. toft
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT! GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO O (O) O (S) LS (40) CO (77.5) TONTRACTOR'S under my jurisdiction a	R PERFORATION OPENITATION OPEN	O in. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W. Wire Wrs. S: From 3.2. S: From 3.2. nent Cemeral Lines cral Lines ss Pool cral Lines cral Li	eight	used (open hole orch Cut	Wall thickn	constructed, recent retue to the best of n	ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORAT! GRAVEL PAG 9 GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO O (O) O (S) IS 40 40 47. S under my jurisdiction a Kansas Water Well Cool	R PERFORATION OPENITION OP	Oin. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W Wire Wre S: From 3.2. S: From 3.2. nent Cemeral Lines case Pool epage Pit Concrete tile PHOLOGIC LOCAL CONTROL	eight	used (open hole orch Cut	Wall thickny Other To Other Trilled Holes Ione (Open Holes The first to other	constructed, recent true to the best of nupleted on (mo-day-y-more)	ft. to
Casing height above land: TYPE OF SCREEN OF Steel Stain Brass Galv SCREEN OR PERFOR Continuous Slot Louvered Shutter SCREEN-PERFORATI GRAVEL PAG GROUT MATERIA Grout Intervals: From Nearest source of possibl Septic Tank Sewer Lines Watertight Sewer Line Watertight Sewer Line Other (Specify) Direction from well? 10 FROM TO O (O) O (O) O (O) O (O) O (O) O (O) CO (O)	Surface	O in. W ON MATERIA Fiberglass Concrete tile NGS ARE: Gauze W Wire Wre S: From .3.2. S: From .3.2. nent Cemeral Lines ss Pool page Pit Line Wire Wre Si / H When Claude Claude Si / H When Claude Si	eight	used (open hole orch Cut D aw Cut N aw Cut	Wall thickny Other To Other Trilled Holes Ione (Open Holes In to Other It to Other It to Other The Istorage Fertilizer Storage TO I	constructed, recent true to the best of nuclear on (mo-day-y	ft. to

KSA 82a-1212

Visit us at http://www.kdheks.gov/waterwell/index.html

Revised 9/10/2012